

Data sheet Product MK 204 34 G



PCB connectors>Male headers

Solder and plug pins, Ø 0.5 mm Also available as single contact, SK ...

Features

pitch:	2.54 x 2.54 mm
no. of contacts:	34
contact material:	CuZn-alloy
surface of contact:	gold-plated
surface contact / contact sleeve:	• Ni+≥0.2µm Au • Ni+4...6µm Sn
version:	with solder-cup
shock resistance:	50 g
volume resistance:	≤10 mΩ
vibration resistance max.:	15 g
capacity between two adjacent contacts:	≤0,4 pF
nominal current:	1.5 A
nominal voltage:	60 V DC
test voltage:	1000 V
insulating body material:	PA 4.6. GF
temperature range:	• -40°C... +163°C • (260°C/10 s)
class of inflammability:	UL 94 V-0
specific insulation resistance:	>10 ⁷ Ω·m
connection type:	THT (Einlöt)

yes

Technical drawing of a mechanical part, showing a cross-section. The drawing includes the following dimensions:

- Overall height: 10,6
- Top section height: 2,54
- Section height: 3,2
- Section height: 4
- Section height: 3,3
- Section height: 2,5
- Section height: 5
- Top diameter: $\varnothing 0,9$
- Section diameter: $\varnothing 1,8$
- Section diameter: $\varnothing 1,35$
- Bottom diameter: $\varnothing 0,5$