

## M12 Cable Assembly D-cod st/- f/- 7,5m



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                     |
|--------------------|-------------------------------------------------------------------------------------|
| Part number        | 21 34 930 0405 075                                                                  |
| Specification      | M12 Cable Assembly D-cod st/- f/- 7,5m                                              |
| HARTING eCatalogue | <a href="https://harting.com/21349300405075">https://harting.com/21349300405075</a> |

### Identification

|               |                                 |
|---------------|---------------------------------|
| Category      | System cabling                  |
| Series        | Circular connectors M12         |
| Element       | Cable assemblies                |
| Specification | Pre-assembled on one side       |
| Connector 1   | M12 D-coding<br>Female Straight |
| Type of cable | Copper cable (round)            |

### Version

|                 |             |
|-----------------|-------------|
| Cable length    | 7.5 m       |
| Number of cores | 4           |
| Core structure  | 4x AWG 22/7 |
| Coding          | D-coding    |

### Technical characteristics

|                              |                              |
|------------------------------|------------------------------|
| Transmission characteristics | Cat. 5 Class D up to 100 MHz |
| Data rate                    | 10 Mbit/s<br>100 Mbit/s      |

### Material properties

|                  |                                                        |
|------------------|--------------------------------------------------------|
| Material (cable) | PVC                                                    |
| Colour (cable)   | Green                                                  |
| RoHS             | compliant with exemption                               |
| RoHS exemptions  | 6(c): Copper alloy containing up to 4 % lead by weight |



**Pushing Performance**  
Since 1945

## Material properties

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| ELV status                           | compliant with exemption             |
| China RoHS                           | 50                                   |
| REACH Annex XVII substances          | Not contained                        |
| REACH ANNEX XIV substances           | Not contained                        |
| REACH SVHC substances                | Yes                                  |
| REACH SVHC substances                | Lead                                 |
| ECHA SCIP number                     | 0d7d3693-d625-47ab-934a-d241bf72c86e |
| California Proposition 65 substances | Yes                                  |
| California Proposition 65 substances | Lead                                 |

## Specifications and approvals

|                |                                                |
|----------------|------------------------------------------------|
| Specifications | UN/ECE-R 118 fire protection for rolling stock |
| Approvals      | CE                                             |

## Commercial data

|                                |                                              |
|--------------------------------|----------------------------------------------|
| Packaging size                 | 1                                            |
| Net weight                     | 541 g                                        |
| Country of origin              | Germany                                      |
| European customs tariff number | 85444290                                     |
| GTIN                           | 5713140145474                                |
| eCl@ss                         | 27060390 Ready-made data cable (unspecified) |
| ETIM                           | EC002599                                     |
| UNSPSC 24.0                    | 26121600                                     |