

9050.4200

Product number

Actuation type	direkt
Weight	6.300 g
Switching function	Wechsler (DPDT Momentary)
Material fixed contact	Ag
Number of poles	2 - pole
Connections	Lötanschluss, abgedichtet
Mechanical life endurance	1E5
Contact system	25E3
Rating IEC	4 A 30 V DC 5 A 48 V AC

Contact resistance (new condition)	< 20 mOhm	
Insulation resistance (new condition)	> 1000 MOhm	
Voltage strength at 250 V	Function insulation / Basic insulation	null V
	Reinforced insulation	null V
	Small contact distance	> 1000 V
Actuators	Drücker, CuZn vernickelt	
Housing description	Sockel: olivgrün, DAP Gewindebuchse: CuZn vernickelt, 6-Kantmuttern aus CuZn vernickelt Zahnscheibe: Duroplast (Sockel) / Stahl verzinkt chromatiert (Bügelplatte) Bügelplatte: Stahl rostfrei	
Connection surface	Bearing connection	versilbert
	External connection	versilbert
Contact material	Ag	
Contact type	Abhebekontakt	
Operating force	≤ 3.6 N	
Miscellaneous	Hub 1.1 mm leichtgängige Ausführung zugehörige Druckknöpfe 9090.16.. siehe Zusatzteile NKK-Nr.: MB-2521	

Type of fastening

Zentralbefestigung M6 x 0.75

All information subject to possible technical changes