


Item no.: 231-370/001-000
 Product description: Male header (for PCBs) Straight solder pin 1.2 x 1.2 mm 10-pole Pin spacing 5.08 mm / 0.2 in Vertical PCB mounting with closed end



Produkt kann von Bild abweichen / product may differ

Packing unit 100 4*25 pieces

RoHS compliant

Product group	3 (Multi Conn. System)
Weight	4.03 g
Color	orange
pole count	10
Height	12 mm
Height	0.472 in
Width	54 mm
Width	2.126 in
Depth	8.4 mm
Depth	0.331 in
Pin spacing from	5.08 mm
Pin spacing from	0.2 in
Rating based on	IEC/EN 60664-1
Overvoltage category EN I	III
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV
Current intensity EN	12 A

Overvoltage category EN II	II
Pollution degree	2
Measured voltage EN	630 V
Measured shock voltage	4 kV



Current intensity EN	12 A
Overvoltage category EN III	III
Degree of pollution	3
Rated voltage EN	320 V
Rated surge voltage	4 kV
Nominal current	12 A
Solder pin length [mm]	5 mm
Solder pin width A [mm]	1.2 mm
Solder pin width B [mm]	1.2 mm
Diameter of drilled hole [mm]	1.7 mm
Tolerance of drilled hole diameter [mm]	0.1 mm
Material group	I
Insulating material	PA 6.6
Temperature stability	-60 °C to +100 °C
Flammability category, based on UL 94	V0
Contact material	Electrolytic copper (Ecu)
Contact plating	tin-plated



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
231-370/001-000	BV	11915/A0	400	16	2,5
231-370/001-000	CCA	5764	250	16	1,2x,21
231-370/001-000	CSA	154112-1466354	300	15	
231-370/001-000	KEMA	2083746.02	250	16	1,2x,21
231-370/001-000	KR	HMB05880-EL003	250/400	12/16	2,5
231-370/001-000	UR	E45171	600	15	
231-370/001-000	UR	E45172	300	15	

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected