



Product information

Erem®

592E

Code No. : **T592E**

Tip cutter - pointed relieved head

- This is the narrowest head shape.
- The underside is relieved and facilitates optimum access even to extremely hard-to-reach areas.

Technical Data

| | |
|---------------------------------|----------------------|
| Cut: | Flush |
| Length: | 115 mm / 4,527 Inch |
| Weight: | 67 g / 2.36 oz. |
| Length of cutting edges: | 12 mm / .472 Inch |
| Head width: | 11 mm / .433 Inch |
| Head thickness: | 6,5 mm / .256 Inch |
| Head length: | 19 mm / .748 Inch |
| Max. cutting capability | |
| Hard wire: | - |
| Medium hardness: | Ø 0,4 mm / .015 Inch |
| Copper wire: | Ø 0,8 mm / .031 Inch |

Series 500 Medium

- Medium-size, robust, precision
- Wide range of head shapes
- Manufactured from high grade tool steel
- Cutting edges hardened to Rockwell 63-65 HRC
- Non reflecting surface, ESDsafe and resharpenable

Erem Cutters and Tip Cutters

- Internal patented Erem Magic Spring
 - Reduce costs by long life
 - Constant spring force
 - Guarantees more than 1 million operations
- High precision screw joint
 - Smooth jaw action with no play
 - Smooth cutting operation with no jaw overlapping
- Induction-hardened cutting edges in Rockwell hardness 63 - 65 HRc for exceptionally long life
- EMOS maximum opening stop limits the cutting-edge tips from opening more than 5 mm / .197 Inch. The limited extent to which the handles can open prevent user hand fatigue.
- Ergonomically shaped handles for high comfort, better grip and added safety
- Erem cut:
 - Options for semi flush, full flush or super flush cuts