



Single-deck terminal block - Stackable version - Pitch 5,08mm - 2÷12 poles

GENERAL INFORMATION

| | |
|------------------------|------------------------------|
| pitch: | 5,08 mm |
| housing height: | 10,60 mm |
| housing depth: | 8.1 mm |
| dimensional class: | slow |
| wire section: | 1.5 mm ² / 16 AWG |
| clamp opening size: | 2.6 × 2 mm |
| wire stripping: | max 6 mm |
| operating temperature: | -40°C ÷ +130°C |

ELECTRICAL CHARACTERISTICS

| | |
|---------------|-------------|
| current: | 13.5A |
| voltage: | 250V |
| test voltage: | 2 kVrms/60s |

MECHANICAL CHARACTERISTICS

| | |
|--------------|---------------------|
| screw: | M3 |
| max. torque: | 0.5 Nm / 4.5 in.lbs |

APPROVALS DATA



EN 60998-1



-



UL 1059

13.5A factory / 10A field

| | | |
|---------------|--------------------|---|
| current: | 13.5A | - |
| voltage: | 250V | - |
| wire section: | 1.5mm ² | - |
| torque: | 0.5Nm | - |
| FILE: | EQ202 | - |

| |
|----------|
| 300V |
| 16÷30AWG |
| 4.5Lb-in |
| E178356 |

MATERIALS

| | |
|----------|------------------|
| housing: | PA - UL 94 V0 |
| screw: | Galvanized steel |

AVAILABLE COLOURS



clamp/spring:
terminal:

Nickeled copper alloy other colours:
Tin-plated copper alloy

upon request

| poles | P/N | pcs/pack | W [Kg]* | W [Kg]* |
|-------|-----------------|----------|---------|---------|
| 2 | MV152-5,08-H-L | N/A | N/A | N/A |
| 3 | MV153-5,08-H-L | N/A | N/A | N/A |
| 4 | MV154-5,08-H-L | N/A | N/A | N/A |
| 5 | MV155-5,08-H-L | N/A | N/A | N/A |
| 6 | MV156-5,08-H-L | N/A | N/A | N/A |
| 7 | MV157-5,08-H-L | N/A | N/A | N/A |
| 8 | MV158-5,08-H-L | N/A | N/A | N/A |
| 9 | MV159-5,08-H-L | N/A | N/A | N/A |
| 10 | MV1510-5,08-H-L | N/A | N/A | N/A |
| 11 | MV1511-5,08-H-L | N/A | N/A | N/A |
| 12 | MV1512-5,08-H-L | N/A | N/A | N/A |