


Item no.: 250-119
 Product description: 1-CONDUCTOR PCB TERMINAL STRIP 1 FRONT SOLDER
 PIN / POLE 19 POLE PIN SPACING 3.5 MM / 0.138 IN WITH
 PUSH BUTTONS WITH TEST SLOT FOR TEST PLUG TO 1.3
 MM Ø



Produkt kann von Bild abweichen / product may differ

Packing unit 60 4*15 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	8.776 g
Color	gray
No. of connection Points	19
No. of potentials	19
pole count	19
Height	13.1 mm
Height	0.516 in
Width	68 mm
Width	2.677 in
Depth	12 mm
Depth	0.472 in
Pin spacing from	3.5 mm
Pin spacing from	0.138 in
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV

Current intensity EN	8 A
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	8 A



Cross section [mm ²]	0.2 - 1.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.2 - 1.5 mm ²
Wiring method	fine-stranded
Cross section [mm ²]	0.25 - 1 mm ²
Wiring method	fine-stranded (with ferrule and plastic collar)
Cross section [mm ²]	0.25 - 1 mm ²
Wiring method	fine-stranded (with ferrule, without plastic collar)
Cross section [AWG]	24 - 16 AWG
Strip length from	8.5 mm
Strip length to	9.5 mm
Material group	I
Contact surface	Copper
xxx-xxx/000-002	yellow
xxx-xxx/000-004	black
xxx-xxx/000-005	red
xxx-xxx/000-006	blue
xxx-xxx/000-009	light gray
xxx-xxx/000-012	orange
xxx-xxx/000-014	brown
xxx-xxx/000-017	light green
xxx-xxx/000-024	violet
xxx-xxx/000-050	white



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
250-119	ABS	04-HG469925/1-PDA	250	2	0,5-1,5
250-119	BV	11915/A0	200	2	0,5-1,5
250-119	CCA	NL6336	250	8	0,2-1,5
250-119	CSA	154112-1132097	300	10	20-16
250-119	DNV	E-9215	250	2	0,5-1,5
250-119	GL	17296-00HH	250	2	0,5-1,5
250-119	KEMA	2114919.01	250	8	0,2-1,5
250-119	UR	E45172	300	5	24-16

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected