

Data sheet

264-130

2-CONDUCTOR EEX E II END TERMINAL BLOCK CENTRE MARKING
FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE



Technical data

Package size 100 pieces.

Cross section from [mm ²]	0.5 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	20 AWG
Cross section to [AWG]	12 AWG
Voltage UL	600 V
Voltage CSA	600 V
Current UL	20 A
Current CSA	20 A
Measured voltage EN	750 V
Current intensity EN	23 A
Weight	3.97 g
Color	light grey
Wiring type	Front-entry
No. of connection Points	2
No. of potentials	1
Height	22 mm
Height	0.867 in
Width	6 mm
Width	0.236 in
Depth	32 mm
Depth	1.26 in
Strip length from	8 mm
Strip length to	9 mm

Data sheet

264-130

**2-CONDUCTOR EEX E II END TERMINAL BLOCK CENTRE MARKING
FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**

Strip length

0.33 in

Data sheet

264-130

2-CONDUCTOR EEX E II END TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

Approval	Voltage	Current	Approval number	Notes
BKI	250	23	94B1-034U	
BKI-Ex	750	23	BKI-Ex-99.C.216U	
BV			07436/C0	
CSA	600	20	18677-23	
cURus-EX	600	20	E185892	
DEMKO		24	120040/120039/04	
GOSENERGO-Ex	750	23	99.041	
KEMA	750		94.7117.01	
KOPALNIA-EX	750	23	KDBNr00.E.235U	
KR	800	24	HMB05880-EL002	
PTB	750	23	IECExPTB04.0003U	
PTB	750	23	PTB98Atex3129U	
SEMKO			9404012	
SEV-EX	275	23	97,550142,1	
UL	600	20	E45172	
VDE	660		3945ÜG,BL.2	

Data sheet

264-130

2-CONDUCTOR EEX E II END TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

Accessories

Item number

ALTERNATE COMB TYPE JUMPER BAR INSULATED	280-492
ALTERNATE COMB TYPE JUMPER BAR INSULATED	281-492
COMB TYPE JUMPER BAR INSULATED	264-402
COVER CARRIER TYPE 1	709-167
COVER TYPE 1	709-153
END PLATE WITH FIXING FLANGE	264-363
Individual wire jumpers	individual jumper
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-002
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-005
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-006
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-007
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-012
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-017
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-023
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-024
Open individual wire jumpers ends	individual jumper open end
OPERATING STICKER FOR FRONT-ENTRY MINIATURE RAIL-MOUNTED TERMINAL BLOCKS	210-291
OPERATING TOOL INSULATED	280-432
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-258
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620
SPARE FIXING / RETAINING SCREWS	209-196
SPARE KNURLED NUT	210-549