



Pushing Performance
Since 1945

M12 X-coded Cable Assembly-7,5m



Image is for illustration purposes only. Please refer to product description.

Part number	21 33 292 9853 075
Specification	M12 X-coded Cable Assembly-7,5m
HARTING eCatalogue	https://harting.com/21332929853075

Identification

Category	System cabling
Series	Circular connectors M12
Identification	PushPull
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	M12 X-coding
	Male Straight
	PushPull
Connector 2	M12 X-coding
	Male Straight
	PushPull
Type of cable	Copper cable (round)
Description of the cable	for railway applications

Version

Cable length	7.5 m
Number of cores	8
Core structure	8x AWG 24/7
Coding	X-coding

Technical characteristics

Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz
------------------------------	--



Pushing Performance
Since 1945

Technical characteristics

Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s
Limiting temperature	-40 ... +80 °C

Material properties

Material (cable)	PE
Colour (cable)	Black
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

Commercial data

Packaging size	1
Net weight	1 g
Country of origin	Romania
European customs tariff number	85444290
GTIN	5713140248342
eCl@ss	27060390 Ready-made data cable (unspecified)
ETIM	EC002599
UNSPSC 24.0	26121600