



## Male plug-in connector - Faston type: 6.3x0.8 - Pitch 5mm - Double PIN - 02÷30 poles

### GENERAL INFORMATION

pitch:	5 mm
housing height:	12,65 mm
housing depth:	9.7 mm
dimensional class:	n/a
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-°C ÷ +°C

### ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	250V
impulse voltage:	4 kV

### MECHANICAL CHARACTERISTICS

### APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	18A factory / 15A field
FILE:	-	-	300V E178356

### MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a

### AVAILABLE COLOURS



other colours: upon request

terminal:

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PVVF02-5-V-D68-1F	N/A	N/A	N/A
03	PVVF03-5-V-D68-1F	N/A	N/A	N/A
04	PVVF04-5-V-D68-1F	N/A	N/A	N/A
05	PVVF05-5-V-D68-1F	N/A	N/A	N/A
06	PVVF06-5-V-D68-1F	N/A	N/A	N/A
07	PVVF07-5-V-D68-1F	N/A	N/A	N/A
08	PVVF08-5-V-D68-1F	N/A	N/A	N/A
09	PVVF09-5-V-D68-1F	N/A	N/A	N/A
10	PVVF10-5-V-D68-1F	N/A	N/A	N/A
11	PVVF11-5-V-D68-1F	N/A	N/A	N/A
12	PVVF12-5-V-D68-1F	N/A	N/A	N/A
13	PVVF13-5-V-D68-1F	N/A	N/A	N/A
14	PVVF14-5-V-D68-1F	N/A	N/A	N/A
15	PVVF15-5-V-D68-1F	N/A	N/A	N/A
16	PVVF16-5-V-D68-1F	N/A	N/A	N/A
17	PVVF17-5-V-D68-1F	N/A	N/A	N/A
18	PVVF18-5-V-D68-1F	N/A	N/A	N/A
19	PVVF19-5-V-D68-1F	N/A	N/A	N/A
20	PVVF20-5-V-D68-1F	N/A	N/A	N/A
21	PVVF21-5-V-D68-1F	N/A	N/A	N/A
22	PVVF22-5-V-D68-1F	N/A	N/A	N/A
23	PVVF23-5-V-D68-1F	N/A	N/A	N/A
24	PVVF24-5-V-D68-1F	N/A	N/A	N/A