

Data sheet

741-904

**MODULAR FEEDTHROUGH END TERMINAL BLOCK 2 SOLDER PINS / POLE
WITH INTEGRATED PUSH BUTTONS AND TOUCH CONTACT TESTING PIN
SPACING 5 MM / 0.197 IN WITHOUT PROTRUDING ASSEMBLY PINS**



Technical data

Package size 600 6*100 pieces.

Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	1
Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	16 A
Measured voltage EN	500 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	16 A
Weight	0.837 g
Color	grey
Wiring type	Side-entry
No. of connection Points	1
No. of potentials	1
Height	18.5 mm
Height	0.728 in
Width	5 mm

Data sheet**741-904****MODULAR FEEDTHROUGH END TERMINAL BLOCK 2 SOLDER PINS / POLE
WITH INTEGRATED PUSH BUTTONS AND TOUCH CONTACT TESTING PIN
SPACING 5 MM / 0.197 IN WITHOUT PROTRUDING ASSEMBLY PINS**

Width	0.197 in
Depth	12.8 mm
Depth	0.504 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in

Data sheet

741-904

**MODULAR FEEDTHROUGH END TERMINAL BLOCK 2 SOLDER PINS / POLE
WITH INTEGRATED PUSH BUTTONS AND TOUCH CONTACT TESTING PIN
SPACING 5 MM / 0.197 IN WITHOUT PROTRUDING ASSEMBLY PINS**

Approval	Voltage	Current	Approval number	Notes
BV	250	16	11915/A0	
CCA	250	16	DK2095	
DEMKO	250	16	99-04158	
DNV	250	16	E6998	
GL	250	16	17296-00HH	

Data sheet

741-904

**MODULAR FEEDTHROUGH END TERMINAL BLOCK 2 SOLDER PINS / POLE
WITH INTEGRATED PUSH BUTTONS AND TOUCH CONTACT TESTING PIN
SPACING 5 MM / 0.197 IN WITHOUT PROTRUDING ASSEMBLY PINS**

Accessories**Item number**

END PLATE SNAP FIT TYPE

741-100

END PLATE SNAP FIT TYPE

741-906

SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm

210-620

Data sheet

741-904

**MODULAR FEEDTHROUGH END TERMINAL BLOCK 2 SOLDER PINS / POLE
WITH INTEGRATED PUSH BUTTONS AND TOUCH CONTACT TESTING PIN
SPACING 5 MM / 0.197 IN WITHOUT PROTRUDING ASSEMBLY PINS**

