



## Male plug-in connector - Faston type: 6.3x0.8 - Pitch 10mm - Double PIN - 02÷15 poles

### GENERAL INFORMATION

pitch:	10 mm
housing height:	12,65 mm
housing depth:	9.7 mm
dimensional class:	n/a
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	A
voltage:	V
test voltage:	kVrms/60s

### MECHANICAL CHARACTERISTICS

### APPROVALS DATA



current:	-	UL 1059
voltage:	-	18A factory / 15A field
FILE:	-	300V E178356

### MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a

### AVAILABLE COLOURS



other colours: upon request

terminal:

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PVSF02-10-V-D68-1F	N/A	N/A	N/A
03	PVSF03-10-V-D68-1F	N/A	N/A	N/A
04	PVSF04-10-V-D68-1F	N/A	N/A	N/A
05	PVSF05-10-V-D68-1F	N/A	N/A	N/A
06	PVSF06-10-V-D68-1F	N/A	N/A	N/A
07	PVSF07-10-V-D68-1F	N/A	N/A	N/A
08	PVSF08-10-V-D68-1F	N/A	N/A	N/A
09	PVSF09-10-V-D68-1F	N/A	N/A	N/A
10	PVSF10-10-V-D68-1F	N/A	N/A	N/A
11	PVSF11-10-V-D68-1F	N/A	N/A	N/A
12	PVSF12-10-V-D68-1F	N/A	N/A	N/A
13	PVSF13-10-V-D68-1F	N/A	N/A	N/A
14	PVSF14-10-V-D68-1F	N/A	N/A	N/A
15	PVSF15-10-V-D68-1F	N/A	N/A	N/A