


Item no.: 736-124
 Product description: DOUBLE DECK PCB TERMINAL STRIP 2 SOLDER PINS IN LINE 24X2 POLE PIN SPACING 5 MM / 0.197 IN



Produkt kann von Bild abweichen / product may differ

Packing unit 14 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	54.24 g
Color	gray
No. of connection Points	48
No. of potentials	48
pole count	24
Height	26.5 mm
Height	1.04 in
Width	121 mm
Width	4.764 in
Depth	21 mm
Depth	0.827 in
Pin spacing from	5 mm
Pin spacing from	0.197 in
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV
Current intensity EN	21 A
Pollution degree	2

Measured voltage EN	630 V
Measured shock voltage	4 kV
Current intensity EN	21 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 2.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [mm ²]	0.25 - 2.5 mm ²
Cross section [AWG]	28 - 12 AWG
Strip length from	5 mm
Strip length to	6 mm
Material group	I



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
736-124	ABS	04-HG469925/1-PDA	250	12	0,5-2,5
736-124	BV	11915/A0	250	12	0,5-2,5
736-124	CCA	NL6266	250	12	0,5-2,5
736-124	CSA	18677-26	300	10	28-12
736-124	DNV	E-9215	250	12	0,5-2,5
736-124	GL	17296-00HH	250	12	0,5-2,5
736-124	KEMA	2110204.06	250	12	0,5-2,5
736-124	UR	E45172	300	10	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected