

Item no.: 770-243
 Product description: Socket without strain relief housing 3-pole Pin spacing 10 mm / 0.394 in 100% protected against mismatching



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

Product group	20 (WINSTA)
pole count	3
Cross section [mm ²]	0.5 - 4 mm ²
Cross section [AWG]	20 - 12 AWG
Connection method	CAGE CLAMP®S Connection
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	25 A
Weight	9.614 g
Color	grey
No. of connection Points	6
No. of potentials	3
Height	12.9 mm
Height	0.508 in
Width	30 mm
Width	1.181 in
Depth	37.5 mm
Depth	1.476 in

Strip length from
Strip length to
Strip length

9 mm
9 mm
0.35 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
770-243	ABS	06-HG154986/11-PDA	250	25	0,5-4,0
770-243	CCA		250	25	0,5-4,0
770-243	cURus	E45171	600	20	12
770-243	KEMA		250	25	0,5-4,0
770-243	PRS	TE/1719/880590/08	250	25	0,5-4,0
770-243	PSE	JET0695-43009-1001	600	20	12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected