



Pushing Performance  
Since 1945

# PPV4 2.0 RJ45 - RJ45 IP20 Cat6A out 0,5m



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                     |
|--------------------|-------------------------------------------------------------------------------------|
| Part number        | 09 48 284 7758 005                                                                  |
| Specification      | PPV4 2.0 RJ45 - RJ45 IP20 Cat6A out 0,5m                                            |
| HARTING eCatalogue | <a href="https://harting.com/09482847758005">https://harting.com/09482847758005</a> |

## Identification

|                          |                               |
|--------------------------|-------------------------------|
| Category                 | System cabling                |
| Series                   | HARTING PushPull (V4)         |
| Element                  | Cable assemblies              |
| Specification            | Pre-assembled on both sides   |
| Connector 1              | HARTING PushPull (V4)<br>RJ45 |
| Connector 2              | RJ45                          |
| Type of cable            | Copper cable (round)          |
| Description of the cable | Wiring 1:1                    |

## Version

|                 |                |
|-----------------|----------------|
| Cable length    | 0.5 m          |
| Number of cores | 8              |
| Core structure  | 4x 2x AWG 26/7 |
| Shielding       | Shielded       |

## Technical characteristics

|                              |                                            |
|------------------------------|--------------------------------------------|
| Transmission characteristics | Cat. 6A Class E <sub>A</sub> up to 500 MHz |
| Data rate                    | 10 Mbit/s                                  |
|                              | 100 Mbit/s                                 |
|                              | 1 Gbit/s                                   |
|                              | 2.5 Gbit/s                                 |
|                              | 5 Gbit/s                                   |
|                              | 10 Gbit/s                                  |



**Pushing Performance**  
Since 1945

## Technical characteristics

|                      |                |
|----------------------|----------------|
| Limiting temperature | -20 ... +70 °C |
|----------------------|----------------|

## Material properties

|                  |       |
|------------------|-------|
| Material (cable) | PVC   |
| Colour (cable)   | Black |

## Specifications and approvals

|                |                                |
|----------------|--------------------------------|
| Specifications | IEC 61076-3-106 Variant 4 (V4) |
|----------------|--------------------------------|

## Commercial data

|                                |                                              |
|--------------------------------|----------------------------------------------|
| Packaging size                 | 1                                            |
| Net weight                     | 52.4 g                                       |
| Country of origin              | Latvia                                       |
| European customs tariff number | 85444290                                     |
| GTIN                           | 5713140391161                                |
| eCl@ss                         | 27060390 Ready-made data cable (unspecified) |
| ETIM                           | EC002599                                     |
| UNSPSC 24.0                    | 26121600                                     |