



Single-deck terminal block - Stackable version - Pitch 7,5mm - 2÷16 poles

GENERAL INFORMATION

pitch:	7,5 mm
housing height:	12,80 mm
housing depth:	8.4 mm
dimensional class:	slow
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.5 x 3 mm
wire stripping:	max 7.5 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	750V
test voltage:	3 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



current:	-	EN 60998-1	UL 1059
voltage:	-	24A	26A factory / 20A field
wire section:	-	750V	300V
torque:	-	2,5mm ²	12÷30AWG
FILE:	-	0,5Nm	4,5Lb-in
		40019705	E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Tin-plated copper alloy
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
-------	-----	----------	---------	---------

2	MVE262-7,5-V-L	N/A	N/A	N/A
3	MVE263-7,5-V-L	N/A	N/A	N/A
4	MVE264-7,5-V-L	N/A	N/A	N/A
5	MVE265-7,5-V-L	N/A	N/A	N/A
6	MVE266-7,5-V-L	N/A	N/A	N/A
7	MVE267-7,5-V-L	N/A	N/A	N/A
8	MVE268-7,5-V-L	N/A	N/A	N/A
9	MVE269-7,5-V-L	N/A	N/A	N/A
10	MVE2610-7,5-V-L	N/A	N/A	N/A
11	MVE2611-7,5-V-L	N/A	N/A	N/A
12	MVE2612-7,5-V-L	N/A	N/A	N/A
13	MVE2613-7,5-V-L	N/A	N/A	N/A
14	MVE2614-7,5-V-L	N/A	N/A	N/A
15	MVE2615-7,5-V-L	N/A	N/A	N/A
16	MVE2616-7,5-V-L	N/A	N/A	N/A