
Item no.: 775-642
Product description: MULTILEVEL INSTALLATION TERMINAL BLOCK L/L



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Product group	17 (TOP JOB INSTALLATION TERMINAL BLOCKS)
Number of levels	3
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [AWG]	28 - 14 AWG
Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 4 mm ²
Cross section [AWG]	28 - 12 AWG
Wiring method	f
Measured voltage EN	400 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	20 A
Current intensity EN	25 A
Weight	10.94 g
Color	gray
Wiring type	Front-entry
No. of connection Points	4
No. of potentials	2
Height	43 mm

Height
Width
Width

1.69 in
5 mm
0.197 in



Depth	91 mm
Depth	3.58 in
Strip length from	6 mm
Strip length to	7 mm
Strip length	0.24 in
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
775-642	ABS	05-HG476175/3-PDA	250/400	24/25	2,5/4,0
775-642	BV	07436/Co	250/400	24/25	2,5/4,0
775-642	CCA	NL5804	400	24/25	2,5/4,0
775-642	DNV	E-10423	250/400	24/25	2,5/4,0
775-642	GL	17295-00HH	250/400	24/25	2,5/4,0
775-642	KEMA	2082859.01	400	24/25	2,5/4,0
775-642	LR	91/20112(E6)	250/400	24/25	2,5/4,0

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected