



Product information

Weller®

Zero Smog 6V mobile fume extraction

Code No. : **T0053667699**

for adhesive fumes volume extraction

Mobile fume extraction unit 230 V / 50 Hz, for volume extraction with built in turbine. For upto 6 workplaces. One connection included, further connections must be ordered separately

*****Approved technology in new design*****

Weller Tools announces design changes for all fume extraction units of the new product line WellerFT

According to the official announcement of the consolidation of Weller Zero-Smog and Filtronic to the new brand WellerFT filter system, all products will be produced in a new unique color.



(change date February 2014)

Technical Data



This station is ESD safe

Dimensions L x B xH: 450 x 450 x 650 mm

Weight: 40 kg

Voltage: 230 V/50 Hz (

Sound level in 1m:	51 dB(A)
Electrical power:	460 VA
Max. vacuum:	2800Pa
Max. capacity:	615 m ³ /h
Fine dust filter:	Fine dust filter F 7
Filter:	Filter for adhesive fumes (wide band gas filter 50% active carbon, 50% Puratex)
RS232 port	All system functions can be operated and remotely monitored via the RS232 port
USBport	<p>The USB port can be used to load firmware updates, run efficiency tests and log data.</p> <p>Do not leave the USB medium inserted for longer than 2 minutes. After this time expires, the USB module will switch off automatically.</p>