



**Product information**

## Erem®

**776E**

Code No. : **T776E**

Side cutter - pointed relieved head

- This is the narrowest head shape.
- The underside is relieved and facilitates optimum access even to extremely hard-to-reach areas.

**Technical Data**

<b>Cut:</b>	Super full flush
<b>Length:</b>	110 mm / 4.331 Inch
<b>Weight:</b>	48 g / 1.69 oz.
<b>Length of cutting edges:</b>	9 mm / .354 Inch
<b>Head width:</b>	9 mm / .354 Inch
<b>Head thickness:</b>	6 mm / .236 Inch
<b>Head length:</b>	15 mm / .590 Inch
<b>Max. cutting capability</b>	
<b>Hard wire:</b>	-
<b>Medium hardness:</b>	Ø 0,6 mm / .023 Inch
<b>Copper wire:</b>	Ø 0,8 mm / .031 Inch

Series 600 Micro

- Miniature cutter
- Offers a wide variety of head shapes for access in difficult to reach areas
- Suitable for SMD and leads (670EP, 670EPF)
- Made from high grade tool steel with cutting edges hardened to 63-65 HRc
- Non-reflecting surface, ESD-safe, resharpenable

Erem Cutters and Tip Cutters

- Internal patented Erem Magic Spring
  - Reduce costs by long life
  - Constant spring force
  - Guarantees more than 1 million operations
- High precision screw joint
  - Smooth jaw action with no play
  - Smooth cutting operation with no jaw overlapping
- Induction-hardened cutting edges in Rockwell hardness 63 - 65 HRc for exceptionally long life
- EMOS maximum opening stop limits the cutting-edge tips from opening more than 5 mm / .197 Inch. The limited extent to which the handles can open prevent user hand fatigue.
- Ergonomically shaped handles for high comfort, better grip and added safety
- Erem cut:
  - Options for semi flush, full flush or super flush cuts