

Data sheet Product SL 11 SMD 052 32 G B SM



PCB connectors>Male headers

□ 0.635 mm

... packing (option) - additions:

SL 11 SMD 040-104 ... SM; ... B SM: 6-40 contacts

SL 11 SMD 040-062 ... B TR: 26-40 contacts, 250 pcs/reel

SL 11 SMD 040-078 ... B TR: 6-24 contacts, **250 pcs/reel**

SL 11 SMD 104-130 ... B TR: 6-24 **contacts**, 150 pcs/reel

Features

pitch:	2.54 x 2.54 mm
--------	----------------

no. of contacts:	32
------------------	----

contact material:	CuSn-alloy
-------------------	------------

surface of contact:	gold-plated
---------------------	-------------

surface contact / contact sleeve:	• Ni+≥0.2µm Au • Ni+4...6µm Sn
--------------------------------------	---

version:	male header
----------	-------------

volume resistance:	≤5 mΩ
--------------------	-------

nominal current:	3 A
------------------	-----

nominal voltage:	250 V AC
------------------	----------

test voltage:	2000 V
---------------	--------

insulating body material:	PA 4.6. GF
---------------------------	------------

temperature range:	• -40°C... +163°C • (260°C/10 s)
--------------------	---

class of inflammability:	UL 94 V-0
--------------------------	-----------

specific insulation resistance:	>10 ⁷ Ω·m
------------------------------------	----------------------

connection type:	SMD
------------------	-----

reflow solderable:	yes
--------------------	-----

pick and place pad and bar magazine

Figure 1 shows three technical drawings of test specimens, labeled (a), (b), and (c), with their dimensions in millimeters.

- (a)** A specimen with a base width of 2,8 mm. The distance between the centers of the pins is $n/2 \times 2,54$ mm. The offset of the pins from the base edge is 0,635 mm. The height of the pins is 5 mm.
- (b)** A specimen with a base width of 8,5 mm. The offset of the pins from the base edge is 3,4 mm. The height of the pins is 5 mm.
- (c)** A specimen with a base width of 9 mm. The offset of the pins from the base edge is 3 mm. The height of the pins is 5 mm.

S: 4.0 mm

Technical drawings of various electronic components and their dimensions:

- SM and B SM components:**
 - Top view: Dimensions include 8,5, 2,54, 7,63, and C.
 - Side view: Dimensions include 6, 5,3, 1,3, 7,3, 3,4, and 8,5.
 - Front view (SM): Dimensions include 17,5 and 13,3.
 - Front view (B SM): Dimensions include 17,5 and 13,3.
- SL 11 SMD 040-062 ... 6-24 ... B TR component:**
 - Top view: Dimensions include 16, 13,8, 4, 44, 40,4, Ø 2, and Ø 1,5.
 - Side view: Dimensions include 11,9 and 7,2.
- SL 11 SMD 040-062 ... 26-40 ... B TR component:**
 - Top view: Dimensions include 16, 4, 11,9, 7,2, 40,4, Ø 2, and Ø 1,5.
 - Side view: Dimensions include 11,9 and 7,2.
- SL 11 SMD 078 ... B TR component:**
 - Top view: Dimensions include 16, 13,1, 4, 44, 40,4, Ø 2, and Ø 1,5.
 - Side view: Dimensions include 19,1 and 7,2.
- SL 11 SMD 104-130 ... 6-24 ... B TR component:**
 - Top view: Dimensions include 16, 20, 19,1, 44, 40,4, Ø 2, and Ø 1,5.
 - Side view: Dimensions include 19,1 and 7,2.