
Item no.: 281-629
Product description: DOUBLE DECK TERMINAL BLOCK THROUGH/THROUGH
SUITABLE FOR EX I APPLICATIONS



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Product group	1 (Rail Mounted Terminal Blocks)
Number of levels	2
Cross section [mm ²]	0.08 - 4 mm ²
Cross section [AWG]	28 - 12 AWG
Connection method	CAGE CLAMP® CONNECTION
Measured voltage EN	500 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	26 A
Weight	14.564 g
Color	blue
Wiring type	Front-entry
No. of connection Points	4
No. of potentials	2
Height	58.5 mm
Height	2.3 in
Width	6 mm
Width	0.236 in
Depth	73.5 mm

Depth	2.89 in
Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
281-629	ABS	05-HG476175/3-PDA	500	26	4,0
281-629	BV	07436/Co	500	26	4,0
281-629	CCA	NL5591/1	500	26	4
281-629	CSA	154112-1505034	600	25	28-12
281-629	DNV	E-10423	800	32	4,0
281-629	KEMA	2076376.01	500	26	4
281-629	KR	HMB05880-EL001	500/800	10/35	4
281-629	LR	91/20112(E6)	500	26	4,0
281-629	PRS	TE/1718/880590/08	500	26	4
281-629	RMR	11130002	500	26	4,0
281-629	UR	E45172	600	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected