



Product information



Code No.: **T599FO**

High precision tool for optical fibres - special tool steel, ESD-safe

- Side cutter, suitable for cutting Kevlar® silks, VectranTM-sheated wires, optical fibres and small stainless wires.

Technical Data

Length:	115 mm / 4.527 Inch
Weight:	67 g / 2.36 oz.
Length of cutting edges:	12 mm / .472 Inch
Head width:	11 mm / .413 Inch
Head thickness:	6,5 mm / .295 Inch
Head length:	19 mm / .748 Inch
Suitable for cutting	g Kevlar® silks.

Erem Cutters and Tip Cutters

- Internal patented Erem Magic Spring
 - Reduce costs by long life
 - Constant spring force
 - Guarantees more than 1 million operations
- High precision screw joint
 - Smooth jaw action with no play
 - Smooth cutting operation with no jaw overlapping
- Induction-hardened cutting edges in Rockwell hardness 63 65 HRc for exceptionally long life
- EMOS maximum opening stop limits the cutting-edge tips from opening more than 5 mm / .197 Inch. The limited extent to which the handles can open prevent user hand fatigue.
- Ergonomically shaped handles for high comfort, better grip and added safety



• Erem cut: Options for semi flush, full flush or super flush cuts

Page 2 / 2