

Data sheet

264-727

**4-CONDUCTOR MINIATURE EARTH CONDUCTOR TERMINAL BLOCK CENTRE
MARKING
FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**



Technical data

Package size 100 pieces.

Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Number of strands	2
Voltage CSA	600 V
Current CSA	20 A
Weight	7.5 g
Color	green-yellow
Wiring type	Front-entry
No. of connection Points	4
No. of potentials	2
Height	24.5 mm
Height	0.96 in
Width	10 mm
Width	0.394 in
Depth	32 mm
Depth	1.26 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in

Data sheet

264-727

4-CONDUCTOR MINIATURE EARTH CONDUCTOR TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

Approval	Voltage	Current	Approval number	Notes
BBJ	800	24	B/12/696/03	
BV			07436/C0	
CCA			DK96-00357	
CSA			18677-23	
CSM	800	24	017956	
cURus-EX			E185892	
DNV	800	24	E6998	
GL			17295-00HH	
KEMA			94.7117.01	
KR	800	24	HMB05880-EL002	
LR	800	24	91/20242(E3)	
NEMKO	750		L94015	
RMR	800	24	99.00007.250	
RosTesT	800	24	B09523	
SEMKO			8928190	
SEV-EX			97,550142,1	
UL			E45172	
VDE	660		3945ÜG,BL.2	

Data sheet

264-727

4-CONDUCTOR MINIATURE EARTH CONDUCTOR TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

Accessories

Item number

ALTERNATE COMB TYPE JUMPER BAR INSULATED	280-492
ALUMINIUM CARRIER RAIL 15 X 5.5 MM, 1 MM / 0.039 IN THICK	210-296
COMB TYPE JUMPER BAR INSULATED	264-402
COVER CARRIER TYPE 1	709-167
COVER TYPE 1	709-153
END AND INTERMEDIATE PLATE 4 MM / 0.157 IN THICK	264-368
END AND INTERMEDIATE PLATE 4 MM / 0.157 IN THICK	264-369
Individual wire jumpers	individual jumper
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-002
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-005
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-006
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-007
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-012
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-017
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-023
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-024
MODULAR TEST PLUG ADAPTER MODULAR	249-139
Open individual wire jumpers ends	individual jumper open end
OPERATING STICKER FOR FRONT-ENTRY MINIATURE RAIL-MOUNTED TERMINAL BLOCKS	210-291
OPERATING TOOL FITTED FOR SERIES 264, 280, 281	209-130
OPERATING TOOL INSULATED	280-432
OPERATING TOOL INSULATED	280-433
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-258
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620
SCREWLESS END STOP FOR WSB QUICK MARKERS	249-101
SPARE FIXING / RETAINING SCREWS	209-196
SPARE KNURLED NUT	210-549
STEEL CARRIER RAIL 15 X 5.5 MM, 1 MM / 0.039 IN THICK	210-111
STEEL CARRIER RAIL 15 X 5.5 MM, 1 MM / 0.039 IN THICK	210-295
STEEL CARRIER RAIL 15 X 5.5 MM, 1 MM / 0.039 IN THICK	210-541
STEEL CARRIER RAIL 15 X 5.5 MM, 1 MM / 0.039 IN THICK	210-542
SYRINGE CONTENT: 20 ml ALU-PLUS CONTACT PASTE	249-130
TEST PLUG 2 MM / 0.079 IN WIDE	210-136
TEST PLUG 2.3 MM / 0.091 IN WIDE	210-137