INTERCHANGEABLE WALL PLUG POWER SUPPLY 5.1VDC 15.3WATT



T7725DV

Features:

- Interchangeable AC Heads
- 1 Year Warranty
- Level VI Efficiency
- Worldwide Approvals



Description:

The Stontronics 5.1Vdc 3Amp Interchangeable Power supply with USB Type C output connector. The unit is finished in Black and comes complete with UK & Euro AC Heads with all the relevant country approvals.

| | Specification |
|--------------------------|---|
| Part Code | T7725DV |
| Input Voltage Range | 90-264 Vac |
| Input Frequency Range | 47-63Hz |
| Input Current Rated | 0.6A Max |
| Input AC Heads | UK & Euro |
| Output Voltage Rating | +5.1V |
| Output Current Max | 3A |
| Output Current Min | 0A |
| Output Connection Type | Plug Type C |
| Total Output Regulation | +/- 5% |
| Line Regulation | +/- 2% |
| Ripple & Noise | 240mVp-p |
| Efficiency | 81.97% Min |
| Over Voltage Protection | 10VDC maximum |
| Over Current Protection | 5 A maximum with auto-recovery function |
| Short-Circuit Protection | The adapter shall not be damaged by short the DC output to Ground |
| Operating Temperature | 0°C to +40°C |
| Storage Temperature | -20°C to +60°C |
| Operating Humidity | 20 to 85% |
| Storage Humidity | 5 to 95% |
| Hi-Pot | 3000VAC 10mA 1min |
| Leakage Current | 0.25mA max |
| Safety Standard | UL/CUL(UL62368) TUV-GS(EN62368) SAA(AS/NZS62368) |
| EMI Standard | FCC(PART 15 CLASS B) CE(EN55032) RCM |
| MTBF | 50K Hours |
| Size mm max. | 74.5 (L) x 36 (W) x 54(H) |
| Weight | 115g ±15% |

INTERCHANGEABLE WALL PLUG POWER SUPPLY 5.1VDC 15.3WATT



T7725DV

Diagrams











