


Item no.: 255-762
 Product description: MODULAR PCB TERMINAL BLOCK 2 SOLDER PINS / POLE
 1 POLE PIN SPACING 10/10.16 MM / 0.4 IN WITH PUSH
 BOTTOMS



Produkt kann von Bild abweichen / product may differ

Packing unit 300 3*100 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	1.63 g
Color	dark gray
No. of connection Points	1
No. of potentials	1
pole count	1
Height	14.2 mm
Height	0.559 in
Width	10 mm
Width	0.394 in
Depth	18.3 mm
Depth	0.72 in
Pin spacing from	10 mm
Pin spacing up to	10.16 mm
Pin spacing from	0.394 in
Pin spacing up to	0.4 in
Pollution degree	2
Measured voltage EN	1000 V

Measured shock voltage	8 kV
Current intensity EN	24 A
Pollution degree	2
Measured voltage EN	1000 V



Measured shock voltage	8 kV
Current intensity EN	24 A
Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 2.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [AWG]	28 - 12 AWG
Strip length from	5 mm
Strip length to	6 mm
Material group	I



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
255-762	ABS	04-HG469925/1-PDA	1000/500	16	0,5-2,5
255-762	BV	11915/A0	1000/500	16	0,08-2,5
255-762	CCA	NL6248	500	24	0,08-2,5
255-762	CSA	18677-45	300	15	28-12
255-762	DNV	E-9215	1000/500	16	0,08-2,5
255-762	GL	17296-00HH	1000/500	16	0,5-2,5
255-762	KEMA	2110204.02	500	16	0,5-2,5
255-762	RMR	11130002	250	16	0,5-2,5
255-762	UR	E45172	300	15	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected