

Item no.: 257-840
 Product description: MODULAR PCB TERMINAL BLOCK 2 SOLDER PINS / POLE
 1 POLE PIN SPACING 5/5.08 MM / 0.2 IN ANGLED LEVER



Produkt kann von Bild abweichen / product may differ

Packing unit 500 5*100 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	1.133 g
Color	red
No. of connection Points	1
No. of potentials	1
pole count	1
Height	20.2 mm
Height	0.795 in
Width	5 mm
Width	0.197 in
Depth	14.2 mm
Depth	0.559 in
Pin spacing from	5 mm
Pin spacing up to	5.08 mm
Pin spacing from	0.197 in
Pin spacing up to	0.2 in
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV

Current intensity EN
Pollution degree
Measured voltage EN

24 A
2
630 V



Measured shock voltage	4 kV
Current intensity EN	24 A
Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 2.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [AWG]	28 - 12 AWG
Strip length from	5 mm
Strip length to	6 mm
Material group	I
Customs Tariff No.	85369010
Country of Origin	Schweiz

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected