



02P 产品匹配此CAP:
925-20-050044

MATERIAL

Contact Pin : Brass

SPECIFICATION

Current Rate : 3 AMP

Insulation Resistance : 5000MΩMin.

Contact Resistance : 20mΩMax.

Dielectric Voltage : AC 500V for one minute

61X-9 2- xx G B E0
1 2 3 4 5 6

1. 5: Normal Parts
- 7: Green Product
- 9: Green Product High Temp
2. 1: Single row
- 2: Dual rows
3. No. of contacts per row
4. G: Gold flash
- T: Tin plated
5. B: Black Insulator
- W: White Insulator
6. Pinrex internal code.

POLES	DIM A	DIM B	POLES	DIM A	DIM B
			21	53.34	50.80
2	5.08	2.54	22	55.88	53.34
3	7.62	5.08	23	58.42	55.88
4	10.16	7.62	24	60.96	58.42
5	12.70	10.16	25	63.50	60.96
6	15.24	12.70	26	66.04	63.50
7	17.78	15.24	27	68.58	66.04
8	20.32	17.78	28	71.12	68.58
9	22.86	20.32	29	73.66	71.12
10	25.40	22.86	30	76.20	73.66
11	27.94	25.40	31	78.74	76.20
12	30.48	27.94	32	81.28	78.74
13	33.02	30.48	33	83.82	81.28
14	35.56	33.02	34	86.36	83.82
15	38.10	35.56	35	88.90	86.36
16	40.64	38.10	36	91.44	88.90
17	43.18	40.64	37	93.98	91.44
18	45.72	43.18	38	96.52	93.98
19	48.26	45.72	39	99.06	96.52
20	50.80	48.26	40	101.60	99.06

REV.	DESCRIPTION	DATE
B	修正CAP結構	2016/07/05
A	RELEASE	2013/08/26

TOLERANCE	
.0	=±.30
.00	=±.20
.000	=±.XXX
.0000=±.	
ANG.=±3'	

UNITS : mm	
SCALE	SIZE
NONE	A4

OLD PART NO.		DRAWER		CHECK	
SHEET		REV.		APP'D	
1 OF 1	B				

TITLE	
FEMALE HEADER 2.54*2.54mm	
SMT TYPE TRIPLE CONTACT	
DUAL ROWS, HEIGHT 8.5mm	
CAP+TAPE REFL	
NEW PART NO.	
61X-92-xxGBE0	

頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.	
DRAW NO.	
61X-92-xxGBE0(B版)	