



Single-deck terminal block - Stackable version - Pitch 5mm - 2÷12 poles

GENERAL INFORMATION

pitch:	5 mm
housing height:	10,60 mm
housing depth:	8.1 mm
dimensional class:	slow
wire section:	1.5 mm ² / 16 AWG
clamp opening size:	2.6 × 2 mm
wire stripping:	max 6 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	13.5A
voltage:	250V
test voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



EN 60998-1



-



UL 1059

13.5A factory / 10A field

current:	13.5A	-
voltage:	250V	-
wire section:	1.5mm ²	-
torque:	0.5Nm	-
FILE:	EQ202	-

300V
16÷30AWG
4.5Lb-in
E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel

AVAILABLE COLOURS



clamp/spring:
terminal:

Nickeled copper alloy
Tin-plated copper alloy

other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MV152-5-H-L	N/A	N/A	N/A
3	MV153-5-H-L	N/A	N/A	N/A
4	MV154-5-H-L	N/A	N/A	N/A
5	MV155-5-H-L	N/A	N/A	N/A
6	MV156-5-H-L	N/A	N/A	N/A
7	MV157-5-H-L	N/A	N/A	N/A
8	MV158-5-H-L	N/A	N/A	N/A
9	MV159-5-H-L	N/A	N/A	N/A
10	MV1510-5-H-L	N/A	N/A	N/A
11	MV1511-5-H-L	N/A	N/A	N/A
12	MV1512-5-H-L	N/A	N/A	N/A