

**Industrial SD H1-M** 



# Apacer

## Industrial SD H1-M

#### **Overview**

Apacer Industrial Secure Digital 3.0 card is ideal for its high performance, good reliability and wide compatibility, not to mention that it's well adapted for hand-held applications in semi-industrial/medical markets already. The H1-M series providing wide range capacities from 4GB to 128GB fully compliant to SD3.0, and SD2.0 specifications are built with MLC NAND Flash and the latest firmware including read disturb , wear leveling & bad block management algorithms .Furthermore, this product also has an optional -45C to 85C extended temperature range version to withstand the extreme environmental condition.



#### Feature

- Compliant with SD 3.0 Specification
- S.M.A.R.T supported
- Wear-Leveling and Block Management
- Support Class 10 with UHS-I
- Power Failure Management
- Auto Read Refresh



### **Specifications**

Model	Industrial SD H1-M
Interface	SD3.0
Form Factor	SD
NAND Flash Type	MLC
Capacity	SDHC:4GB~128GB
Sustained Read Performance (MB/sec)	Up to 43
Sustained Write Performance (MB/sec)	Up to 25
ECC Engine	Built-in 42-bit per 1K bytes BCH ECC
Standard Operating Temperature ( °C )	-25 ~ + 85
Extended Operating Temperature ( °C )	-40 ~ + 85
Storage Temperature ( °C )	-40 ~ + 85
Shock	(Operating)1,500G, 0.5ms
Vibration	20Hz~80Hz/1.52mm (frequency/displacement) 80Hz~2,000Hz/20G (frequency/accelerate)
Operating Voltage	3.3 V ± 5%
Power Consumption	Active mode: 145 mA & Idle mode: 235 uA
Dimension (L x W x H )	32x24x2.1 (mm)
MTBF (hours)	>3,000,000

### For more information, contact your Apacer representative

#### **Global Presence**

Taiwan (Headquarters) Apacer Technology Inc. Tel: +886-2-2267-8000 Fax: +886-2-2267-2261

Apacer Technology B.V. Tel: +31-40-267-0000 Fax: +31-40-290-0686

Apacer Memory America, Inc. Tel: +1-408-518-8699 Fax: 1-510-249-9551

China Apacer Electronic(Shanghai) Co., Ltd. Tel: +86-21-6228-9939

Apacer Technology Corp.

Tel: +81-3-5419-2668 Fax: +81-3-5419-0018 Apacer Technologies Pvt. Ltd. Tel: +91-80-41529061~3 Fax: +91-80-41700215