

Male headers

Sandwich-design

- "S" selective gold-plated up to 33 mm pin length
- for interconnections of stacked PCBs
- within the total length of the pin the insulator position can be changed as required ... **Design specification-sheet**
- **separable!** any requested number of contact can be delivered

- one row, □ 0,635 mm

art. no.	dim. [mm]		art. no.	dim. [mm]		art. no.	dim. [mm]	
	A	L		A	L		A	L
SL 5 071 ...	7.1	16.4	SL 5 172 ...	17.2	26.5	SL 5 315 ...	31.5	40.8
SL 5 097 ...	9.7	19.0	SL 5 197 ...	19.7	29.0	SL 5 360 ...	36.0	45.3
SL 5 121 ...	12.1	21.4	SL 5 223 ...	22.3	31.6	SL 5 415 ...	41.5	50.8
SL 5 147 ...	14.7	24.0	SL 5 237 ...	23.7	33.0	SL 5 525 ...	52.2	61.5
SL 5 156 ...	15.6	24.9	SL 5 285 ...	28.5	37.8			

please indicate:

- ... no. of contacts one row 1 - 36
- ... surface of contact
 S = selective gold-plated
 G = gold-plated
 Z = tin-plated

- two rows, □ 0,635 mm

art. no.	dim. [mm]		art. no.	dim. [mm]		art. no.	dim. [mm]	
	A	L		A	L		A	L
SL 6 071 ...	7.1	16.4	SL 6 172 ...	17.2	26.5	SL 6 315 ...	31.5	40.8
SL 6 097 ...	9.7	19.0	SL 6 197 ...	19.7	29.0	SL 6 360 ...	36.0	45.3
SL 6 121 ...	12.1	21.4	SL 6 223 ...	22.3	31.6	SL 6 415 ...	41.5	50.8
SL 6 147 ...	14.7	24.0	SL 6 237 ...	23.7	33.0	SL 6 525 ...	52.2	61.5
SL 6 156 ...	15.6	24.9	SL 6 285 ...	28.5	37.8			

please indicate:

- ... no. of contacts two rows 2 - 72
- ... surface of contact
 S = selective gold-plated
 G = gold-plated
 Z = tin-plated