


# UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ground terminal, number of connections: 2, connection method: Screw connection, cross section: 0.2 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: green-yellow

## Your advantages

- The large wiring space enables the connection of solid and stranded conductors without ferrules, even above the nominal cross section
- As well as saving space, the compact design enables user-friendly wiring in a small amount of space
- Optimum screwdriver guidance through closed screw shafts
- Tested for railway applications
- The cable entry funnel enables the use of conductors with ferrules and plastic collars within the nominal cross section

## Commercial data

Item number	3044157
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE1
Product key	BE1121
Catalog page	Page 173 (C-1-2019)
GTIN	4017918960414
Weight per piece (including packing)	22.1 g
Weight per piece (excluding packing)	21.6 g
Customs tariff number	85369010
Country of origin	DE

# UT 6-PE - Ground terminal



3044157

<https://www.phoenixcontact.com/sk/products/3044157>

## Technical data

### Product properties

Product type	Ground terminal block
Area of application	Railway industry
	Machine building
	Plant engineering
	Process industry
Number of connections	2
Number of rows	1

### Data management status

Article revision	17
------------------	----

### Insulation characteristics

Overvoltage category	III
Degree of pollution	3

### Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	1.31 W

### Connection data

Grounding foot	Yes
Number of connections per level	2
Nominal cross section	6 mm <sup>2</sup>
Rated cross section AWG	8

### Level 1 above 1 below 1

Screw thread	M4
Note	Please observe the current carrying capacity of the DIN rails.
Tightening torque	1.5 ... 1.8 Nm
Stripping length	10 mm
Internal cylindrical gage	A5
Connection in acc. with standard	IEC 60947-7-2
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 10 mm <sup>2</sup>
Cross section AWG	24 ... 6 (converted acc. to IEC)
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 10 mm <sup>2</sup>
Conductor cross section, flexible [AWG]	24 ... 8 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Flexible conductor cross section (ferrule with plastic sleeve)	0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Note	Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.

### Ex data

# UT 6-PE - Ground terminal



3044157

<https://www.phoenixcontact.com/sk/products/3044157>

## Rated data (ATEX/IECEX)

Identification	⊕ II 2 GD Ex eb IIC Gb
Operating temperature range	-60 °C ... 110 °C
Ex-certified accessories	3047028 D-UT 2,5/10
	1205066 SZS 1,0X4,0 VDE
	3022276 CLIPFIX 35-5
	3022218 CLIPFIX 35
output	(Permanent)

## Ex connection data General

Torque range	1.5 Nm ... 1.8 Nm
Nominal cross section	6 mm <sup>2</sup>
Rated cross section AWG	10
Connection capacity rigid	0.2 mm <sup>2</sup> ... 10 mm <sup>2</sup>
Connection capacity AWG	24 ... 8
Connection capacity flexible	0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Connection capacity AWG	24 ... 10

## Dimensions

Width	8.2 mm
End cover width	2.2 mm
Height	47.7 mm
Depth	46.9 mm
Depth on NS 35/7,5	47.5 mm
Depth on NS 35/15	55 mm

## Material specifications

Color	green-yellow
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

## Mechanical properties

### Mechanical data

Open side panel	Yes
-----------------	-----

## Environmental and real-life conditions

### Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2018-05
Spectrum	Service life test category 2, bogie-mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$
ASD level	6.12 (m/s <sup>2</sup> )/Hz
Acceleration	3.12g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis

### Shocks

Pulse shape	Half-sine
Acceleration	30g
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)

### Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

## Standards and regulations

Connection in acc. with standard	IEC 60947-7-2
----------------------------------	---------------

## Mounting

Mounting type	NS 35/7,5
	NS 35/15

# UT 6-PE - Ground terminal


3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## Drawings

Circuit diagram



# UT 6-PE - Ground terminal



3044157

<https://www.phoenixcontact.com/sk/products/3044157>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sk/products/3044157>

<b>DNV</b> Approval ID: TAE00001S9				
---------------------------------------	--	--	--	--

<b>CSA</b> Approval ID: 13631				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
Use group B	-	-	24 - 8	-
Use group C	-	-	24 - 8	-

<b>IECEE CB Scheme</b> Approval ID: DE1-63045				
--	--	--	--	--

<b>cULus Recognized</b> Approval ID: E60425				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
Use group B	-	-	24 - 8	-
Multi-conductor connection	-	-	24 - 12	-
Use group C	-	-	24 - 8	-
Multi-conductor connection	-	-	24 - 12	-
Use group D	-	-	24 - 8	-
Multi-conductor connection	-	-	24 - 12	-

<b>VDE Gutachten mit Fertigungsüberwachung</b> Approval ID: 40013715				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
Use group keine	-	-	-	0.2 - 6

<b>ATEX</b> Approval ID: KEMA04ATEX2048U				
---	--	--	--	--


# UT 6-PE - Ground terminal




3044157


<https://www.phoenixcontact.com/sk/products/3044157>

	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
Use group keine				
Only flexible conductors	-	-	-	0.2 - 6
Only rigid conductors	-	-	-	0.2 - 10

 <b>cUL Recognized</b> Approval ID: E192998				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
Use group B				
	-	-	24 - 8	-
Use group C				
	-	-	24 - 8	-

 <b>EAC Ex</b> Approval ID: RU C-DE.HA91.B.00066				
--	--	--	--	--

 <b>IECEx</b> Approval ID: IECEx KEM 06.0027U				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
Use group keine				
Only flexible conductors	-	-	-	0.2 - 6
Only rigid conductors	-	-	-	0.2 - 10

 <b>UL Recognized</b> Approval ID: E192998				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
Use group B				
	-	-	24 - 8	-
Use group C				
	-	-	24 - 8	-

 <b>CCC</b> Approval ID: 2020322313000622				
---	--	--	--	--

 <b>UKCA-EX</b> Approval ID: DEKRA 21UKEX0304U				
--	--	--	--	--

# UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



cULus Recognized



# UT 6-PE - Ground terminal



3044157

<https://www.phoenixcontact.com/sk/products/3044157>

## Classifications

### ECLASS

ECLASS-11.0	27141141
ECLASS-13.0	27250103

### ETIM

ETIM 9.0	EC000901
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# UT 6-PE - Ground terminal



3044157

<https://www.phoenixcontact.com/sk/products/3044157>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	6213f14d-5bbe-4eb7-9d0c-693d87d680af

# UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## Accessories

### FBS 2-8 - Plug-in bridge

3030284

<https://www.phoenixcontact.com/sk/products/3030284>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: red

---

### FBS 3-8 - Plug-in bridge

3030297

<https://www.phoenixcontact.com/sk/products/3030297>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: red

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## FBS 5-8 - Plug-in bridge

3030310

<https://www.phoenixcontact.com/sk/products/3030310>

Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: red



---

## FBS 6-8 - Plug-in bridge

3032470

<https://www.phoenixcontact.com/sk/products/3032470>

Plug-in bridge, pitch: 8.2 mm, number of positions: 6, color: red



## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## FBS 10-8 - Plug-in bridge

3030323

<https://www.phoenixcontact.com/sk/products/3030323>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: red

---

## FBSRH 2-8 - Short-circuit connector

3033802

<https://www.phoenixcontact.com/sk/products/3033802>



Short-circuit connector, pitch: 8.2 mm, number of positions: 2, color: red

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## FBSRH 3-8 - Short-circuit connector

3033803

<https://www.phoenixcontact.com/sk/products/3033803>



Short-circuit connector, pitch: 8.2 mm, number of positions: 3, color: red

---

## FBSRH 4-8 - Short-circuit connector

3033804

<https://www.phoenixcontact.com/sk/products/3033804>



Short-circuit connector, pitch: 8.2 mm, number of positions: 4, color: red

# UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## FBSR 2-8 - Plug-in bridge

3033808

<https://www.phoenixcontact.com/sk/products/3033808>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: red

---

## FBSR 3-8 - Plug-in bridge

3001597

<https://www.phoenixcontact.com/sk/products/3001597>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: red

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## FBSR 4-8 - Plug-in bridge

3000585

<https://www.phoenixcontact.com/sk/products/3000585>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: red

---

## FBSR 5-8 - Plug-in bridge

3033809

<https://www.phoenixcontact.com/sk/products/3033809>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: red



## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## FBSR 10-8 - Plug-in bridge

3001599

<https://www.phoenixcontact.com/sk/products/3001599>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: red

---

## FBS 2-8 CT - Plug-in bridge

3033830

<https://www.phoenixcontact.com/sk/products/3033830>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: orange

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## FBS 3-8 CT - Plug-in bridge

3033831

<https://www.phoenixcontact.com/sk/products/3033831>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: orange

---

## FBS 4-8 CT - Plug-in bridge

3033832

<https://www.phoenixcontact.com/sk/products/3033832>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: orange

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## FBS 10-8 CT - Plug-in bridge

3033833

<https://www.phoenixcontact.com/sk/products/3033833>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: orange

---

## SB-MER 2-8 - Switching jumper

3000587

<https://www.phoenixcontact.com/sk/products/3000587>



Switching jumper, pitch: 8.2 mm, number of positions: 2, length: 25 mm, color: gray/orange

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## SB-MER 3-8 - Switching jumper

3000588

<https://www.phoenixcontact.com/sk/products/3000588>



Switching jumper, pitch: 8.2 mm, number of positions: 3, length: 25 mm, color: gray/orange

---

## SB-MER 4-8 - Switching jumper

3000589

<https://www.phoenixcontact.com/sk/products/3000589>



Switching jumper, pitch: 8.2 mm, number of positions: 4, length: 25 mm, color: gray/orange

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## FBS 2-8 BU - Plug-in bridge

3032567

<https://www.phoenixcontact.com/sk/products/3032567>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: blue

---

## FBS 3-8 BU - Plug-in bridge

3032570

<https://www.phoenixcontact.com/sk/products/3032570>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: blue

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## FBS 4-8 BU - Plug-in bridge

3032583

<https://www.phoenixcontact.com/sk/products/3032583>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: blue

---

## FBS 5-8 BU - Plug-in bridge

3032596

<https://www.phoenixcontact.com/sk/products/3032596>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: blue

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## FBS 6-8 BU - Plug-in bridge

3032677

<https://www.phoenixcontact.com/sk/products/3032677>



Plug-in bridge, pitch: 8.2 mm, number of positions: 6, color: blue

---

## FBS 10-8 BU - Plug-in bridge

3032606

<https://www.phoenixcontact.com/sk/products/3032606>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: blue

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## D-UT 2,5/10 - End cover

3047028

<https://www.phoenixcontact.com/sk/products/3047028>

End cover, depth: 39.8 mm, width: 2.2 mm, height: 47 mm, color: gray



---

## ATP-UT - Partition plate

3047167

<https://www.phoenixcontact.com/sk/products/3047167>

Partition plate, depth: 45.7 mm, width: 2.2 mm, height: 53.4 mm, color: gray





## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## PAI-4 - Test adapter

3030925

<https://www.phoenixcontact.com/sk/products/3030925>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: gray

---

## LPS-8/E - Service connector

3270560

<https://www.phoenixcontact.com/sk/products/3270560>



Service connector, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: red

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## LPS-8 - Service connector

3270561

<https://www.phoenixcontact.com/sk/products/3270561>



Service connector, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: red

---

## LPO 6/E - Pick-off plug

3270525

<https://www.phoenixcontact.com/sk/products/3270525>



Pick-off plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## LPO 6 - Pick-off plug

3270526

<https://www.phoenixcontact.com/sk/products/3270526>



Pick-off plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray

---

## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/sk/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/sk/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/sk/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/sk/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/sk/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/sk/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/sk/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/sk/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

---

## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/sk/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>

## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/sk/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/sk/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver



## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/sk/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

---

## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/sk/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/sk/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

---

## NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/sk/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/sk/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/sk/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/sk/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



---

## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/sk/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## ZB 8:UNBEDRUCKT - Zack marker strip

1052002

<https://www.phoenixcontact.com/sk/products/1052002>




Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

---

## ZB 8 CUS - Zack marker strip

0825011

<https://www.phoenixcontact.com/sk/products/0825011>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## UC-TM 8 - Marker for terminal blocks

0818072

<https://www.phoenixcontact.com/sk/products/0818072>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

---

## UC-TM 8 CUS - Marker for terminal blocks

0824597

<https://www.phoenixcontact.com/sk/products/0824597>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

# UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## UCT-TM 8 - Marker for terminal blocks

0828740

<https://www.phoenixcontact.com/sk/products/0828740>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

---

## UCT-TM 8 CUS - Marker for terminal blocks

0829616

<https://www.phoenixcontact.com/sk/products/0829616>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

# UT 6-PE - Ground terminal

3044157


<https://www.phoenixcontact.com/sk/products/3044157>



## ZB 8,LGS:FORTL.ZAHLEN - Zack marker strip

1052015

<https://www.phoenixcontact.com/sk/products/1052015>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10. 5 x 8.15 mm, Number of individual labels: 10

---

## ZB 8,QR:FORTL.ZAHLEN - Zack marker strip

1052028

<https://www.phoenixcontact.com/sk/products/1052028>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10. 5 x 8.15 mm, Number of individual labels: 10



## UT 6-PE - Ground terminal

3044157


<https://www.phoenixcontact.com/sk/products/3044157>



## ZB 8,LGS:L1-N,PE - Marker for terminal blocks

1052413

<https://www.phoenixcontact.com/sk/products/1052413>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

---

## PAI-4-FIX BU - Test adapter

3032729

<https://www.phoenixcontact.com/sk/products/3032729>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: blue

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## PAI-4-FIX OG - Test adapter

3034455

<https://www.phoenixcontact.com/sk/products/3034455>



4 mm test adapter, for terminal blocks with 8.2 mm pitch

---

## PAI-4-FIX YE - Test adapter

3032745

<https://www.phoenixcontact.com/sk/products/3032745>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: yellow

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## PAI-4-FIX RD - Test adapter

3032732

<https://www.phoenixcontact.com/sk/products/3032732>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: red

---

## PAI-4-FIX GN - Test adapter

3032758

<https://www.phoenixcontact.com/sk/products/3032758>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: green

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## PAI-4-FIX BK - Test adapter

3032774

<https://www.phoenixcontact.com/sk/products/3032774>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: black

---

## PAI-4-FIX GY - Test adapter

3032790

<https://www.phoenixcontact.com/sk/products/3032790>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: gray

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## PAI-4-FIX VT - Test adapter

3032761

<https://www.phoenixcontact.com/sk/products/3032761>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: violet

---

## PAI-4-FIX BN - Test adapter

3032787

<https://www.phoenixcontact.com/sk/products/3032787>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: brown

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## PAI-4-FIX WH - Test adapter

3032797

<https://www.phoenixcontact.com/sk/products/3032797>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: white

---

## PAIS-4-FIX GY - Test adapter

3032791

<https://www.phoenixcontact.com/sk/products/3032791>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: gray

# UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## PAIS-4-FIX BK - Test adapter

3032792

<https://www.phoenixcontact.com/sk/products/3032792>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: black

---

## PAIS-4-FIX RD - Test adapter

3032793

<https://www.phoenixcontact.com/sk/products/3032793>



Test adapter, Do not plug in while the power is connected, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: red

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## PAIS-4-FIX BU - Test adapter

3032798

<https://www.phoenixcontact.com/sk/products/3032798>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: blue

---

## PAIS-4-FIX YE - Test adapter

3032799

<https://www.phoenixcontact.com/sk/products/3032799>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: yellow



## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



### PAIS-4-FIX GN - Test adapter

3032801

<https://www.phoenixcontact.com/sk/products/3032801>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: green

---

### PAIS-4-FIX VT - Test adapter

3032802

<https://www.phoenixcontact.com/sk/products/3032802>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: violet

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## PS-8 - Test plug

3031005

<https://www.phoenixcontact.com/sk/products/3031005>

Test plug, Modular test plug, number of positions: 1, color: red



---

## DP PS-8 - Spacer plate

3036741

<https://www.phoenixcontact.com/sk/products/3036741>

Spacer plate, depth: 29 mm, width: 8.2 mm, height: 22.4 mm, number of positions: 1, color: red



## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## PS-8/2,3MM RD - Test plug

3048564

<https://www.phoenixcontact.com/sk/products/3048564>



Test plug, number of positions: 1, color: red

---

## SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/sk/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## X-PEN 0,35 - Marker pen

0811228

<https://www.phoenixcontact.com/sk/products/0811228>



Marker pen without ink cartridge, for manual labeling of markers, labeling extremely wipe-proof, line thickness 0.35 mm

---

## WS UT 6 - Warning label

3047345

<https://www.phoenixcontact.com/sk/products/3047345>

Warning sign for UT terminal blocks



## UT 6-PE - Ground terminal

3044157

<https://www.phoenixcontact.com/sk/products/3044157>



## PROJECT COMPLETE - Software

1050453

<https://www.phoenixcontact.com/sk/products/1050453>



Intuitive planning and marking software for configuring terminal strips and for professional marking of marking materials for terminal blocks, conductors, cables, devices, and systems. The software is available for download

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT s.r.o.

Námestie Mateja Korvína 1

811 07 Bratislava

+421 2 3210 1470

[obchod.sk@phoenixcontact.com](mailto:obchod.sk@phoenixcontact.com)