

SK 5,08/3,8: 0-9 - Marker card




0804303

<https://www.phoenixcontact.com/pc/products/0804303>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Marker card, Sheet, white, labeled, horizontal: consecutive numbers 0 ... 9, mounting type: adhesive, for terminal block width: 5.08 mm, text field height: 3.8 mm, text field width: 5.08 mm



Commercial data

Item number	0804303
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	BG2123
Catalog page	Page 502 (CL-2009)
GTIN	4017918124151
Weight per piece (including packing)	0.9 g
Weight per piece (excluding packing)	0.72 g
Customs tariff number	49119900
Country of origin	PL

SK 5,08/3,8: 0-9 - Marker card



0804303

<https://www.phoenixcontact.com/pc/products/0804303>

Technical data

Product properties

Product type	Labeled terminal marker
Pitch	5.08 mm
Type	adhesive

Data management status

Article revision	02
------------------	----

Marking

Number of marker strips	12
Printing direction	horizontal
Printing	consecutive numbers 0 ... 9

Mounting

Mounting type	adhesive
---------------	----------

Material specifications

Foil strength	53 µm
Adhesive strength	20 µm
Adhesive	Acrylic
Color	white (RAL 9010)
Material	Polyester
Components	free from silicone and halogen

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07 DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

SK 5,08/3,8: 0-9 - Marker card



0804303

<https://www.phoenixcontact.com/pc/products/0804303>

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-40 °C ... 150 °C
Ambient temperature (assembly)	> 15 °C
Recommended storage conditions	23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

Dimensions

Width	5.08 mm
Text field width	5.08 mm
Height	3.8 mm
Text field height	3.80 mm
Pitch	5.08 mm

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Notes

Order information:	For labeling according to customer requirement, please select 0825125 product
--------------------	---

SK 5,08/3,8: 0-9 - Marker card



0804303

<https://www.phoenixcontact.com/pc/products/0804303>

Classifications

ECLASS

ECLASS-11.0	27281101
ECLASS-12.0	27281101
ECLASS-13.0	27281101

ETIM

ETIM 9.0	EC000761
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

SK 5,08/3,8: 0-9 - Marker card



0804303

<https://www.phoenixcontact.com/pc/products/0804303>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com