



Male plug-in connector - Vertical - Dual row - Pitch 5,08mm - 02÷12 poles

GENERAL INFORMATION

pitch:	5,08 mm
housing height:	22,30 mm
housing depth:	28.82 mm
dimensional class:	medium
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	10A
voltage:	500V
impulse voltage:	6 kV

MECHANICAL CHARACTERISTICS

APPROVALS DATA



EN 61984

current:	12A
voltage:	250V
FILE:	CA02.04178



EN 61984

current:	12A
voltage:	250V
FILE:	40005779



UL 1059

current:	12A factory / 12A field
voltage:	300V
FILE:	E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a

AVAILABLE COLOURS



other colours: upon request

terminal:

Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PDV02-5,08	N/A	N/A	N/A
03	PDV03-5,08	N/A	N/A	N/A
04	PDV04-5,08	N/A	N/A	N/A
05	PDV05-5,08	N/A	N/A	N/A
06	PDV06-5,08	N/A	N/A	N/A
07	PDV07-5,08	N/A	N/A	N/A
08	PDV08-5,08	N/A	N/A	N/A
09	PDV09-5,08	N/A	N/A	N/A
10	PDV10-5,08	N/A	N/A	N/A
11	PDV11-5,08	N/A	N/A	N/A
12	PDV12-5,08	N/A	N/A	N/A