

Style E 6.3 (1/4").



7045 Z Standard bit, TORX®, style E 6.3.

Material: High grade chrome-vanadium steel, through hardened.
 Drive: DIN 3126, ISO 1173, style E 6.3.
 Application: For all types of screw applications in trade and industry.

Order-No.	⊕	↔	▬	€/pc.
32299 1	T5	50	5	3.03
32302 8	T6	50	5	3.03
32303 5	T7	50	5	3.03
32304 2	T8	50	5	3.03
32305 9	T9	50	5	3.03
32306 6	T10	50	5	3.03
32307 3	T15	50	5	3.03
32308 0	T20	50	5	3.03
32309 7	T25	50	5	3.03
33920 3	T27	50	NEW	5 3.03
33923 4	T30	50	NEW	5 3.03
33928 9	T40	50	NEW	5 3.03

Style E 6.3 (1/4").



7045 Z TR Standard bit, TORX® H, style E 6.3.

Material: High grade chrome-vanadium steel, through hardened.
 Drive: DIN 3126, ISO 1173, style E 6.3.
 Application: For all types of screw applications in trade and industry.
 Extra: Hole in the bit tip for TORX® Tamper Resistant security screws.

Order-No.	⊕	↔	▬	€/pc.
21045 8	T7H	50	5	3.95
21047 2	T8H	50	5	3.95
20218 7	T9H	50	5	3.95
20219 4	T10H	50	5	3.95
24867 3	T15H	50	5	3.95
20220 0	T20H	50	5	3.95
20221 7	T25H	50	5	3.95
20222 4	T27H	50	5	3.95
20223 1	T30H	50	5	3.95
20224 8	T40H	50	5	3.95



NEW

7045 Z L Standard bit, TORX®, style E 6.3.

Material: High grade chrome-vanadium steel, through hardened.
 Drive: DIN 3126, ISO 1173, style E 6.3.
 Application: For all types of screw applications in trade and industry.

Order-No.	⊕	↔	▬	€/pc.
33709 4	T6	70	5	4.40
33717 9	T6	90	5	5.45
33710 0	T7	70	5	4.40
33718 6	T7	90	5	5.45
33711 7	T8	70	5	4.40
33719 3	T8	90	5	5.45
33712 4	T9	70	5	4.40
33720 9	T9	90	5	5.45
33713 1	T10	70	5	4.40
33721 6	T10	90	5	5.45
33725 4	T10	110	5	6.60
33726 1	T10	150	5	7.65
33714 8	T15	70	5	4.40
33722 3	T15	90	5	5.45
33727 8	T15	110	5	6.60
33728 5	T15	150	5	7.65
33715 5	T20	70	5	4.40
33723 0	T20	90	5	5.45
33729 2	T20	110	5	6.60
33730 8	T20	150	5	7.65
33716 2	T25	70	5	4.40
33724 7	T25	90	5	5.45
33731 5	T25	110	5	6.60
33732 2	T25	150	5	7.65
33921 0	T27	70	5	4.40
33922 7	T27	90	5	5.45
33924 1	T30	70	5	4.40
33925 8	T30	90	5	5.45
33926 5	T30	110	5	6.60
33927 2	T30	150	5	7.65
33929 6	T40	70	5	4.40
33930 2	T40	90	5	5.45
33931 9	T40	110	5	6.60
33932 6	T40	150	5	7.65



7046 Z Standard bit, TORX PLUS®, style E 6.3.

Material: High grade chrome-vanadium steel, through hardened.
 Drive: DIN 3126, ISO 1173, style E 6.3.
 Application: For all types of screw applications in trade and industry.
 Extra: Reinforced profile cross-section transfers approx. 25% more torque than with a TORX® profile.

Order-No.	⊕	↔	▬	€/pc.
28481 7	5IP	50	5	4.50
26000 2	6IP	50	5	4.50
26002 6	7IP	50	5	4.50
23195 8	8IP	50	5	4.50
23197 2	9IP	50	5	4.50
23199 6	10IP	50	5	4.50
23201 6	15IP	50	5	4.50
23203 0	20IP	50	5	4.50
23205 4	25IP	50	5	4.50
23207 8	27IP	50	5	4.50
23209 2	30IP	50	5	4.50
23211 5	40IP	50	5	4.50