

Item no.: 731-604
Product description: MALE CONNECTOR 4 POLE PIN SPACING 7.5 MM / 0.295 IN



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Weight	7.42 g
Color	gray
No. of connection Points	4
No. of potentials	4
pole count	4
Height	14.3 mm
Height	0.563 in
Width	30.7 mm
Width	1.209 in
Depth	27.5 mm
Depth	1.083 in
Pin spacing from	7.5 mm
Pin spacing from	0.295 in
Pollution degree	2
Measured voltage EN	630 V
Measured shock voltage	6 kV
Current intensity EN	12 A
Pollution degree	2
Measured voltage EN	1000 V

Measured shock voltage
Current intensity EN
Connection method

6 kV
12 A
CAGE CLAMP® CONNECTION



Cross section [mm ²]	0.08 - 2.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.08 - 2.5 mm ²
Wiring method	fine-stranded
Cross section [mm ²]	0.25 - 1.5 mm ²
Wiring method	fine-stranded (with ferrule and plastic collar)
Cross section [mm ²]	0.25 - 2.5 mm ²
Wiring method	fine-stranded (with ferrule, without plastic collar)
Cross section [AWG]	28 - 12 AWG
Strip length from	8 mm
Strip length to	9 mm
Material group	I
Contact material	Electrolytic copper (Ecu)
Contact surface	tin-plated
xxx-xxx/033-000	Strain relief plate 20 mm



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
731-604	BV	11915/A0	400	16	0,08-2,5
731-604	CCA	5764	400	16	0,08-2,5
731-604	CSA	154112-1466354	300	15	22-12
731-604	DNV	E-9218	400	12	0,08-2,5
731-604	GL	17296-00HH	400	12	0,08-2,5
731-604	KEMA	2083746.02	400	16	0,08-2,5
731-604	LR	96/20035	400	12	0,08-2,5
731-604	RMR	11130002	400	12	0,08-2,5
731-604	UR	E45171	600	15	28-12
731-604	UR	E45172	300	15	22-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected