

# 9450.0150

## Product number

Actuation type	direkt
Weight	.300 g
Switching function	Wechsler (SPDT Momentary)
Material fixed contact	vergoldet
Number of poles	1 - pole
Connections	Leiterplattenanschluss, abgedichtet
Contact system	5E4
Rating IEC	<math>\leq 0.4V A 28 V</math>
Contact resistance (new condition)	< 80 mOhm

<b>Insulation resistance (new condition)</b>	> 500 MΩ	
<b>Voltage strength at 250 V</b>	Function insulation / Basic insulation Reinforced insulation Small contact distance	null V null V > 500 V
<b>Protection type</b>	Connection Actuator	waschbar waschbar
<b>Actuators</b>	Drücker, weiß, Thermoplast	
<b>Housing description</b>	Gehäuse: schwarz, Thermoplast glasfaserverstärkt	
<b>Connection surface</b>	Bearing connection External connection	vergoldet vergoldet
<b>Contact material</b>	vergoldet	
<b>Contact type</b>	Schiebekontakt	
<b>Operating force</b>	1.7 N	
<b>Total travel / stroke</b>	1.0 mm	
<b>Miscellaneous</b>	NKK-Nr.: GB-15AP	

**Type of fastening**

Leiterplattenmontage

All information subject to possible technical changes