

## Data sheet

741-911

**MODULAR FEEDTHROUGH TERMINAL BLOCK 2 SOLDER PINS / POLE  
WITH INTEGRATED PUSH BUTTONS AND TOUCH CONTACT TESTING PIN  
SPACING 5.08 MM / 0.2 IN FRONT-ENTRY**



## Technical data

Package size 600 6\*100 pieces.

|                                       |                      |
|---------------------------------------|----------------------|
| Pin spacing from                      | 5.08 mm              |
| Pin spacing from                      | 0.2 in               |
| pole count                            | 1                    |
| Cross section from [mm <sup>2</sup> ] | 0.08 mm <sup>2</sup> |
| Cross section to [mm <sup>2</sup> ]   | 2.5 mm <sup>2</sup>  |
| Cross section from [AWG]              | 28 AWG               |
| Cross section to [AWG]                | 12 AWG               |
| Voltage UL                            | 300 V                |
| Voltage CSA                           | 300 V                |
| Current UL                            | 10 A                 |
| Current CSA                           | 16 A                 |
| Measured voltage EN                   | 250 V                |
| Measured shock voltage                | 4 kV                 |
| Pollution degree                      | 3                    |
| Current intensity EN                  | 16 A                 |
| Measured voltage EN                   | 500 V                |
| Measured shock voltage                | 4 kV                 |
| Pollution degree                      | 2                    |
| Current intensity EN                  | 16 A                 |
| Weight                                | 2.58 g               |
| Color                                 | orange               |
| Wiring type                           | Side-entry           |
| No. of connection Points              | 1                    |

---

**Data sheet**

741-911

**MODULAR FEEDTHROUGH TERMINAL BLOCK 2 SOLDER PINS / POLE  
WITH INTEGRATED PUSH BUTTONS AND TOUCH CONTACT TESTING PIN  
SPACING 5.08 MM / 0.2 IN FRONT-ENTRY**

---

|                   |          |
|-------------------|----------|
| No. of potentials | 1        |
| Height            | 18.5 mm  |
| Height            | 0.728 in |
| Width             | 5.08 mm  |
| Width             | 0.2 in   |
| Depth             | 12.8 mm  |
| Depth             | 0.504 in |
| Strip length from | 5 mm     |
| Strip length to   | 6 mm     |
| Strip length      | 0.22 in  |

---

**Data sheet**

741-911

**MODULAR FEEDTHROUGH TERMINAL BLOCK 2 SOLDER PINS / POLE  
WITH INTEGRATED PUSH BUTTONS AND TOUCH CONTACT TESTING PIN  
SPACING 5.08 MM / 0.2 IN FRONT-ENTRY**

---

| <b>Approval</b> | <b>Voltage</b> | <b>Current</b> | <b>Approval number</b> | <b>Notes</b> |
|-----------------|----------------|----------------|------------------------|--------------|
| BV              | 250            | 16             | 11915/A0               |              |
| CCA             | 250            | 16             | DK2095                 |              |
| CSA             | 300            | 16             | 18677-48               |              |
| DEMKO           | 250            | 16             | 99-04158               |              |
| DNV             | 250            | 16             | E6998                  |              |
| GL              | 250            | 16             | 17296-00HH             |              |
| UL              | 300            | 10             | E45172                 |              |

---

**Data sheet**

741-911

**MODULAR FEEDTHROUGH TERMINAL BLOCK 2 SOLDER PINS / POLE  
WITH INTEGRATED PUSH BUTTONS AND TOUCH CONTACT TESTING PIN  
SPACING 5.08 MM / 0.2 IN FRONT-ENTRY**

---

**Accessories****Item number**

END PLATE SNAP FIT TYPE

741-600

END PLATE SNAP FIT TYPE

741-916

SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm

210-620

Data sheet

741-911

**MODULAR FEEDTHROUGH TERMINAL BLOCK 2 SOLDER PINS / POLE  
WITH INTEGRATED PUSH BUTTONS AND TOUCH CONTACT TESTING PIN  
SPACING 5.08 MM / 0.2 IN FRONT-ENTRY**

