



Version with antirotation pegs is available on 2 poles connections.
Disponibile per connessioni a 2 poli versioni con perni antitorsione.

Single-deck terminal block - Stackable version - Pitch 7,62mm - 2÷6 poles

GENERAL INFORMATION

pitch:	7,62 mm
housing height:	8,50 mm
housing depth:	7.3 mm
dimensional class:	slow
wire section:	1.0 mm ² / 16 AWG
clamp opening size:	1.8 × 1.8 mm
wire stripping:	max 6 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	17,5A
voltage:	450V
test voltage:	2.5 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M2
max. torque:	0.2 Nm / 1.8 in.lbs

APPROVALS DATA



EN 60998-1

current: 13.5A

voltage: 450V

wire section: 1.0mm²

torque: 0.2Nm

FILE: CA02.04718



-
-
-
-
-



UL 1059
12A factory / 10A field
300V
16÷30AWG
1.8Lb-in
E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Tin-plated copper alloy
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MV132-7,62-V-L	N/A	N/A	N/A
3	MV133-7,62-V-L	N/A	N/A	N/A
4	MV134-7,62-V-L	N/A	N/A	N/A
5	MV135-7,62-V-L	N/A	N/A	N/A
6	MV136-7,62-V-L	N/A	N/A	N/A