

TWN3 HID PROX

125kHz Contactless Reader



The TWN3 HID PROX transponder reader is designed for easy integration into various applications.

The device supports either USB or RS232 communication just in dependence on the connection cable and is available as ready-to-connect desktop reader in a slim line black or white housing or as a OEM board (PCB) without housing for direct integration into embedded applications.



Readers can be programmed with a script language for autonomous execution of even complex commands like login procedures, increment/decrement functions and many more.

Technical Data

Housing	Material ABS UL94-V0, colour black or white
Frequency	125 kHz
Dimensions	Desktop Reader: 88mm x 56mm x 18mm / 3.5inch x 2.2inch x 0.7inch OEM Board: 76mm x 49mm x 14mm / 3.0inch x 1.9inch x 0.6inch
Power Supply	5V \pm 10% via communication cable (USB); serial version requires external power supply
Supply Current	130mA typ. (USB, normal operation); 220mA peak
Temperature Range	Storage: -45°C up to +85°C (-49°F up to 185°F) Operating: -25°C up to +80°C (-13°F up to 176°F)
Antenna	Aircoil
R/W Distance	up to 100 mm / 4 inch (depending on transponder)
Host Interfaces	USB, RS232
OS Support	Windows XP, Windows Vista, Windows 7 (32/64 bit) and Linux
Communication Parameters	USB: Full speed (12 MBit) RS232: Baudrate: 1200, 2400, 4800, 9600 Parity: none, even, odd
Modes of Operation	USB keyboard emulation USB virtual COM port (bi-directional communication) Direct access to built-in RFID module (transparent mode)
Special Features	Powerful scripting language
Supported Transponders	HID Prox This includes all HID short and long formats, as well as the highly secure Corporate 1000 card formats.
Certifications	CE, R&TTE, RoHS-II compliant, FCC, IC, ACA, VCCI
Weight	Approximately 15g (without housing)
Order Code	OEM board Desktop reader: ART11048 USB black: ART11229 USB white: ART11230 Serial black: ART12457 Serial white: ART12458

¹⁾UID only

Accessories

Order Code	Snap-in holder ART13512 black, ART15344 white		Bracket Holder ART15203 black, ART15235 white		ART11493 USB cable 200cm / 78.74inch ART13488 USB cable 45cm / 17.72inch ART13829 USB cable 120cm / 47.24inch
Order Code	ART14712 Power Supply (EU) ART14714 Power Supply (AU)		ART14713 Power Supply (US) ART14715 Power Supply (UK)		ART14269 USB cable mini 12cm / 4.72inch ART12240 RS232 cable 200cm / 78.74inch

Drawing/Pin Out

Refer to document DS_TWN3 Reader Family Pinouts

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification. Disclaimer: All names are registered trademarks. © 2014 Elatec GmbH – DocRev3 – 02/2014