





Code No. : **T575E**

Tip cutter - angled narrow head

- Suitable for fine cutting work on hybrid circuits or miniature components.

Technical Data

Cut:	Flush
Length:	110 mm / 4.331 Inch
Weight:	67 g / 2.36 oz.
Angle:	45°
Length of cutting edges:	4 mm / .157 Inch
Head width:	11 mm / .433 Inch
Head thickness:	6,5 mm / .256 Inch
Head length:	22 mm / .866 Inch
Max. cutting capability	
Hard wire:	-
Medium hardness:	Ø 0,2 mm / .007 Inch
Copper wire:	Ø 0,6 mm /.023 Inch

Series 500 Medium

- Medium-size, robust, precision
- Wide range of head shapes
- Manufactured from high grade tool steel
- Cutting edges hardened to Rockwell 63-65 HRc
- Non reflecting surface, ESDsafe and resharpenable

Erem Cutters and Tip Cutters



- Internal patented Erem Magic Spring
 - Reduce costs by long life
 - Constant spring force
 - Guarantees more than 1 million operations
- High precision screw joint
 - Smooth jaw action with no play
 - Smooth cutting operation with no jaw overlapping
- Induction-hardened cutting edges in Rockwell hardness 63 65 HRc for exceptionally long life
- EMOS maximum opening stop limits the cutting-edge tips from opening more than 5 mm / .197 Inch. The limited extent to which the handles can open prevent user hand fatigue.
- Ergonomically shaped handles for high comfort, better grip and added safety
- Erem cut:
 Options for semi flush, full flush or super flush cuts