## New 2010.

Available as of February 26, 2010 POS support: • VDE expertise brochure • Display



## Wiha SoftFinish®electric slimVario.

For all work on or around electrical components up to 1000 V AC.

<complex-block></complex-block>		<b>slim</b> 28311 / 0.8x4.0 wiha			2	6.0 283100		V	viha	
SoftFinish® electric slimVario.• VDE exchange bits plus SoftFinish® electric hand-heli screwdriver for the perfect screwdriver for the perfect 		Slim Slim 2011/05/00 withe Slim 2011/05/702 withe Slim 2011/05/702 withe		Bit: Standards: Application: Extra:	Insulation High qualities black finish the bit and Manufactu For all wor The partice enables lo and operation screws be 6 mm VDE	n <sup>®</sup> electric 1000 V A0 ty chrome	slimVario C, VDE-tee vanadium- irated prot y integrate IEC 6090 und electri iameter of ening elerr The slim fc jer and hai	sted and v molybdenu ective insu d in the fro 0:2004. ical compo the bit with hents and s rrm of the b nd guards.	vith GS mark. Im steel, throu- lation is direct ont area. onents up to 10 h integrated pi spring termina bit allows easy	igh hardened, ly moulded onto 000 V AC. rotective insulation ls to be reached reaching of the
• VDE exchange bits plus SoftFinish <sup>®</sup> electric hand-hel screwdriver • Compact sets with six different exchange bits (length 90 mm) • Protective insulation is com- pletely integrated in the front screwdriver • Compact sets with six different exchange bits (length 90 mm) • Sets are 35% lighter than comparable sets • Maximum service life due to lo- cking mechanism of long-life metal parts • Precise work: additional gui- dance with free-running sleeve • SoftFinish <sup>®</sup> electric simVario bit holder with handle, 60 mm. Blade: Chrome-vanadium steel, through-hardened. Insulaton moulded directly onto blade. Handle: • What SoftFinish <sup>®</sup> electric multi-component handle with rol-off protection. Bit holder: Clicik quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits. Note: <td>Ц Ц</td> <td></td> <td></td> <td>Order-No.</td> <td></td> <td></td> <td></td> <td>۲</td> <td></td> <td></td>	Ц Ц			Order-No.				۲		
SoftFinish® electric hand-held screwdriver for the perfect screwdriver • Compact sets with six different exchange bits (length 90 mm) • Sets are 35% lighter than comparable sets • Maximum service life due to lo- cking mechanism of long-life metal parts • Precise work: additional gui- dance with free-running sleeve • Individually tested in water bath at 0,000 volts according to IEC 60900:2004 • Maximum service life due to lo- cking mechanism of long-life metal parts • Precise work: additional gui- dance with free-running sleeve • Via SoftFinish® electric stim/Vario bit holder with handle, 6.0 mm. Biade: • Chrome-vanadium steel, through-hardened, insulation moulded directly onto blade. Handle: • Wha SoftFinish® electric stim/Vario bit holder with nandle, 6.0 mm. Bid holder: • Order-No. • Order-No.	S Wiha	a SoftFinish® electric slimVario.			2831-10	VDE	interchar	igeable bi	t, slotted	
screwdriver for the perfect screwdriver screwdriver • Compact sets with six different • Compact sets with six different comparable sets • Maximum service life due to lo- cking mechanism of long-life metal parts • Precise work: additional gui- dance with free-running sleeve • Precise work: additional gui- dance with free-running sleeve • Precise work: additional gui- dance with free-running sleeve • SoftFinish® electric slimVario bit holder with handle, 6.0 mm. Blade: • Compact serverwhere together with VDE interchangeable bits. Note: • Not for use with bit forms C 6.3 and E 6.3. • Order-No. • Series • SoftFinish® electric multi-component handle with roll-off protection. Bit holder: • Order-No. • Soft Finish® electric multi-component handle with roll-off protection. Bit holder: • Order-No. • Soft Finish® electric multi-component handle bits. Note: • Not for use with bit forms C 6.3 and E 6.3. • Order-No. • Soft Finish® electric multi-component handle bits. Note: • Not for use with bit forms C 6.3 and E 6.3. • Order-No. • Soft Finish® electric multi-component handle bits. Note: • Not for use with bit forms C 6.3 and E 6.3. • Order-No. • Soft Finish® electric multi-component handle bits. • Not for use with bit forms C 6.3 and E 6.3. • Order-No. • Soft Finish® electric multi-component handle bits. • Not for use with bit forms C 6.3 and E 6.3. • Order-No. • Soft Finish® electric multi-component handle bits. • Not for use with bit forms C 6.3 and E 6.3. • Order-No. • Soft Finish® electric multi-component handle bits. • Not for use with bit forms C 6.3 and E 6.3. • Order-No. • Soft Finish® electric multi-component handle bits. • Not for use with bit forms C 6.3 and E 6.3. • Order-No. • Soft Finish® electric multi-component handle bits. • Order-No. • Soft Finish® el				<b>34578</b> 5	⊖; ⊕ 0.4	4 x 2.5	90	6.0	no slim-version	1
screwdriverParticulary slim diameter of 38 mm allows easy access to by lying fastering elements or spring terminalsParticulary slim diameter of 38 mm allows easy access to by lying fastering elements or spring terminals $448815 \oplus Ct 0 10.x 55 90 6.0 1$ • Sets are 35% lighter than comparable sets• Individually tested in water bath at 10.000 volts according to IEC 60900:2004• Diation allows elements or spring terminals• Individually tested in water bath at 10.000 volts according to IEC 60900:2004• Diation allows elements or spring terminals• Precise work: additional gui- dance with free-running sleeve• Precise work: additional gui- dance with free-running sleeve• Diation allows elements or blade.• Diation allows elements or blade. <b>2831-00</b> SottFinish* electric slimVario bit holder with handle, 6.0 mm.• Diation allows elements or to blade.• Diation allows elements or blade.• Diation allows elements or blade. <b>2831-00</b> SottFinish* electric slimVario bit holder with nol-off protection.• Diation allows elements or blade.• Diation allows elements or blade. <b>2831-00</b> SottFinish* electric slimVario bit holder securely locks bits. Only for 6 mm VDE interchangeable bits.• Diation allows elements of blade allows elements of blade allows elements of blade allows elements or blade.• Diation allows elements of blade. <b>2831-00</b> Wins definish*• Diation allows elements of blade allows elements of blade allows elements of blade allows• Diation allows elements elements of blade allows <b>2831-00</b> <td></td> <td></td> <td>d in the front</td> <td><b>34579</b> 2</td> <td>⊖; ⊕ 0.8</td> <td>5 x <b>3.0</b></td> <td>90</td> <td>6.0</td> <td>no slim-version</td> <td>1</td>			d in the front	<b>34579</b> 2	⊖; ⊕ 0.8	5 x <b>3.0</b>	90	6.0	no slim-version	1
• Compact sets with six different exchange bits (length 90 mm) • FaintCutary shift using a sequences to low lying fastening elements or spring terminals • Individually tested in water bath at 10,000 volts according to itC 60900:2004 • Precise work: additional guidance with free-running sleeve • Precise work: additional guidance with free-running sleeve • Precise work: additional guidance with free-running sleeve • SoftFinish® electric slimWario bit holder with handle, 6.0 mm. Elade: • Chrome-vanadium steel, through-hardened. Insulation moulded directly onto bala. • Note: • Not for use with bit forms C 6.3 and E 6.3. • WineWerkzege Combing 2453 - 10 • Note: • Not for use with bit forms C 6.3 and E 6.3. • WineWerkzege Combing 2453 - 10 • WineWerkzege Combing 2453 - 50 • Not for use with bit forms C 6.3 and E 6.3. • WineWerkzege Combing 277.8 6 • 50 • 10 </td <td></td> <td>• · · · ·</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>1</td>		• · · · ·								1
<ul> <li>exchange bits (length 90 mm)</li> <li>• Sets are 35% lighter than comparable sets</li> <li>• Individually tested in water bath at 10,000 volts according to IEC 60900:2004</li> <li>• Precise work: additional guidance with free-running sleeve</li> <li>• Precise work: additional guidance with free-running sleeve</li> <li>• SoftFinish<sup>0</sup> electric simVario bit holder with handle, 6.0 mm.</li> <li>Blade: Chrome-vanadium steel, through-hardened. Insulation moulded directly onto blade.</li> <li>Handle: Wiha SoftFinish<sup>0</sup> electric multi-component handle with roll-off protection.</li> <li>Bit holder: ClicFx quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits.</li> <li>Note: Not for use with bit forms C 6.3 and E 6.3.</li> <li>Order-No. Series</li> <li>Grder-No. Series</li> <li>Grder-N</li></ul>		• Faiticulary Stilling		<b>34581</b> 5			90	6.0		1
<ul> <li>Sets are 35% lighter than comparable sets</li> <li>Maximum service life due to to character of the comparable sets</li> <li>Maximum service life due to to character of the comparable sets</li> <li>Maximum service life due to to character of the comparable sets</li> <li>Maximum service life due to to character of the comparable sets</li> <li>Precise work: additional guidance with free-running sleeve</li> <li>SoftFinish® electric sulfvario bit holder with handle, 6.0 mm.</li> <li>Blade: Chrome-vanadium steel, through-hardened. Insulation moulded directly onto blade.</li> <li>Handlie: Wha SoftFinish® electric multi-component handle with roll-off protection.</li> <li>Bit holder: ClicFix quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits.</li> <li>Note: Not for use with bit forms C 6.3 and E 6.3.</li> <li>Wha Verkeuge GmbH Operated as 3-7 Distribution of the secure of the secure</li></ul>			<b>34582</b> 2						1	
• Individually tested in water bath at 10,000 volts according to the date bath at 10,000 volts according to at 34584 6 $\oplus$ PH2 90 6.0 1 1 43599 1 $\oplus$ 34597 8 $\oplus$ 30,00 34507 8 $\oplus$ 30 $\oplus$ 30 34577 8 $\oplus$ 50 160 30 $\oplus$ 34577 8 $\oplus$ 50 160 30 $\oplus$ 34578 $\oplus$ 50 160 30 $\oplus$ 34578 $\oplus$ 50 160 30 $\oplus$ 34578 $\oplus$ 50 16					2831-11	VDE	interchan	igeable bi	t, Phillips	
At 10,000 volts according to LC 60900:2004At 10,000 volts according to Store work: additional gui- dance with free-running sleeveAtt 10,000 volts according to Store work: additional gui- dance with free-running sleeveAtt 10,000 volts according to Store work: additional gui- dance with free-running sleeveAtt 200 Colspan="2">SottFinish® electric slimVario bit holder with handle, 6.0 mm.Bade: Order-No.Order-No. SeriesOrder-No. SeriesSottFinish® electric multi-component handle with roll-off protection. Bit holder: Other work volte together with VDE interchangeable bits. Note: Not for use with bit forms C 6.3 and E 6.3.Order-No. SeriesSeries Sats77 8Order-No. 5 0 10 0 30 5Series 2 3831-101 1X2.5 1X3.0 1X4.0 1X5.5 1X6.5 4733 5 2 831 1T03 1 1With Merchange and Compact screwdriver together with VDE interchangeable bits. Note: Not for use with bit forms C 6.3 and E 6.3.Order-No. 5 0 2 2831-10 1X3.0 1X4.0 1X5.5 1X6.5Order-No. 2 2831-10 1X3.0 1X4.0 1X5.5 1X6.5Diffection multi-component handleOrder-No. 5 0 3				<b>34583</b> 9	$\oplus$					1
IEC 60900:2004cking mechanism of long-life metal parts• Precise work: additional gui- dance with free-running sleeve2831-00SoftFinish® electric slmVario bit holder with handle, 6.0 mm.Blade: onto blade.Chrome-vanadium steel, through-hardened. Insulation moulded directly onto blade.Handle:Wha SoftFinish® electric nulti-component handle with roll-off protection.Bit holder:ClicFix quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits.Note: <t< td=""><td colspan="3" rowspan="2">Maximum service life due to lo     at 10,000 volts according to</td><td><b>34584</b> 6</td><td>Ð</td><td></td><td></td><td></td><td></td><td></td></t<>	Maximum service life due to lo     at 10,000 volts according to			<b>34584</b> 6	Ð					
$\begin{array}{c} \text{Metal parts} \\ \text{Precise work: additional guidance with free-running sleeve} \\ \hline \\ \text{Masses and the free-running sleevee} \\ \hline \\ \text{Masses and the free-running sleevee} \\ \hline \\ Masses and the$					2831-14	VDE	interchan	igeable bi	t, Xeno (slotte	ed/Pozidriv)
• Precise work: additional guidance with free-running sleeve <b>2831-00</b> SoftFinish <sup>®</sup> electric slimVario bit holder with handle, 6.0 mm. Elade: Chrome-vanadium steel, through-hardened. Insulation moulded directly onto blade. Handle: Wiha SoftFinish <sup>®</sup> electric multi-component handle with roll-off protection. Bit holder: ClicFix quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits. Note: Not for use with bit forms C 6.3 and E 6.3. <b>Order-No. O O O O O O O O O O</b>	cking m	echanism of long-life IEC 60900:2004		34589 1	🛞 Sl	_/PZ 1	90	6.0		1
Also a valuation as set:Also a valuation of a set:Order-No.SeriesSoftFinish® electric slimVario bit holder with handle, 6.0 mm.Blade:Chrome-vanadium steel, through-hardened. Insulation moulded directly onto blade.Handle:Wina SoftFinish® electric multi-component handle with roll-off protection.Bit holder:ClicFix quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits.Application:Compact screwdriver together with VDE interchangeable bits.Not for use with bit forms C 6.3 and E 6.3.Corder-No.SeriesOrder-No.Series34734 52831-101x2.51x3.01x4.01x2.51x3.01x4.01x2.51x3.01x4.01x2.51x3.01x4.01x2.51x3.01x4.01x2.51x3.01x4.01x2.51x3.01x4.01x2.51x3.01x4.01x2.5 <t< td=""><td></td><td></td><td></td><td><b>34590</b> 7</td><td>🛞 Sl</td><td>_/PZ 2</td><td>90</td><td>6.0</td><td></td><td>1</td></t<>				<b>34590</b> 7	🛞 Sl	_/PZ 2	90	6.0		1
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $				Also available	e as set:					
34733 8 $2831 T701$ 12831-00SoftFinish® electric slimVario bit holder with handle, 6.0 mm. $0.2831-10$ $1x3.0$ $1x4.0$ $1x5.5$ $1x6.5$ Blade:Chrome-vanadium steel, through-hardened. Insulation moulded directly onto blade. $0.2831-00$ Bit holder with handle $0.2831-00$ Bit holder with handleHandle:Wiha SoftFinish® electric multi-component handle with roll-off protection. $0.2831-00$ Bit holder with handle $0.2831-00$ Bit holder with handleApplication:Compact screwdriver together with VDE interchangeable bits. $0.2831-10$ $1x2.5$ $1x3.0$ $1x4.0$ $1x5.5$ Note:Not for use with bit forms C 6.3 and E 6.3. $0.2831-00$ Bit holder with handle $0.2831-00$ Bit holder with handleOrder-No. $0.2831-00$ $0.50$ $0.2831-00$ Bit holder with handle $0.2831-00$ $0.2831-00$ $0.2831-00$ Mina Werkzeuge GmbH $0.2831-00$ $0.50$ $0.2831-00$ Bit holder with handle $0.2831-00$ $0.2831-00$ $0.2831-00$ $0.2831-00$ Wina Werkzeuge GmbH $0.2831-00$ $0.50$ $0.2831-00$ Bit holder with handle $0.2831-00$ $0.2831-00$ $0.2831-00$ $0.2831-00$ Wina Werkzeuge GmbH $0.2831-00$ $0.2831-00$ $0.2831-00$ $0.2831-00$ $0.2831-00$ $0.2831-00$ $0.2831-00$ P-78136 Schonach/Germany $0.2831-00$ $0.2831-00$ $0.2831-00$ $0.2831-00$ $0.2831-00$ $0.2831-00$ I to 2831-10 $0.2831-10$ $1.3.0$ $1x4.0$ $1x5.5$ $1x$	uance w	in nee-running steeve			<b>&amp;</b> @4	AC 1000V	4			
2331-00       SoftFinish® electric slimVario bit holder with handle, 6.0 mm.         Blade:       Chrome-vanadium steel, through-hardened. Insulation moulded directly onto blade.         Handle:       Wiha SoftFinish® electric multi-component handle with roll-off protection.         Bit holder:       ClicFix quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits.         Application:       Compact screwdriver together with VDE interchangeable bits.         Note:       Not for use with bit forms C 6.3 and E 6.3.         Order-No.       O         Order-No.       O         Astor7 8       6         50       160         Viha Werkzeuge GmBH         Partalstrafe 3-7         D-78138 Schonach/Germany Tel. + 49 7722 959-0 Fex. + 97722 959-159 info@wiha.com www.whac.com         Partalstrafe 3-7         D-78138 Schonach/Germany Tel. + 49 7722 959-159 info@wiha.com www.whac.com         Partalstrafe 3-7         D-78138 Schonach/Germany Tel. + 49 7722 959-159 info@wiha.com         Fax. + 49 7722 959-159         Partalstrafe 3-7         D-78138 Schonach/Germany Tel. + 49 7722 959-159         Partalstrafe 3-7         D-78138 Schonach/Germany Tel. + 49 7722 959-159         Partalstrafe 3-7         D-78138 Schonach/Germany Tel. + 49 7722 959-159         Partalstrafe 3-7 <td></td> <td></td> <td></td> <td>Order-No.</td> <td>Series</td> <td></td> <td></td> <td></td> <td></td> <td></td>				Order-No.	Series					
Biade: Chrome-vanadium steel, through-hardened. Insulation moulded directly onto blade. Handle: Wiha SoftFinish® electric multi-component handle with roll-off protection. Bit holder: ClicFix quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits. Application: Compact screwdriver together with VDE interchangeable bits. Note: Not for use with bit forms C 6.3 and E 6.3. Order-No. $\bigcirc$ $\Rightarrow$ $\Rightarrow$ $\bigcirc$ $\bigcirc$ 2831-10 1x2.5 1x3.0 1x4.0 1x5.5 $\bigcirc$ 2831-00 Bit holder with handle Order-No. $\bigcirc$ $\Rightarrow$ $\Rightarrow$ $\bigcirc$ $\Rightarrow$ 2831-10 1x2.5 1x3.0 1x4.0 1x5.5 $\bigcirc$ 2831-00 Bit holder with handle Order-No. $\bigcirc$ $\Rightarrow$ $\Rightarrow$ $\bigcirc$ $\bigcirc$ 2831-00 Bit holder with handle $\bigcirc$ $\bigcirc$ 2831-10 1x3.0 1x4.0 1x5.5 1x6.5 $\bigcirc$ 2831-11 1xSL/PZ1 1xSL/PZ2				<b>34733</b> 8	2831 T70	1				1
Blade:Chrome-vanadium steel, through-hardened. Insulation moulded directly onto blade. $\oplus$ $2831-11$ $1xPH1$ $1xPH2$ Handle:Wiha SoftFinish® electric multi-component handle with roll-off protection. $\oplus$ $2831-00$ $Bit$ holder with handleBit holder:ClicFix quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits. $\bigcirc$ $2831-10$ $1xPH2$ Application:Compact screwdriver together with VDE interchangeable bits. $\bigcirc$ $2831-10$ $1x2.5$ $1x3.0$ $1x4.0$ $1x5.5$ Note:Not for use with bit forms C 6.3 and E 6.3. $\bigcirc$ $2831-10$ $Bit holder with handle$ $\bigcirc$ $2831-10$ $1x2.5$ $1x3.0$ $1x4.0$ $1x5.5$ $\bigcirc$ $2831-10$ $Bit holder with handle$ $\bigcirc$ $2831-10$ $Bit holder with handle$ $\bigcirc$ $\bigcirc$ $Order-No.$ $\bigcirc$ $\bigcirc$ $2831-10$ $1x2.5$ $1x3.0$ $1x4.0$ $1x5.5$ $\bigcirc$ $\bigcirc$ $\bigcirc$ $\bigcirc$ $2831-10$ $Bit holder with handle$ $\bigcirc$ <t< td=""><td>2831-00</td><td>SoftFinish<sup>®</sup> electric slimVario bit holder with har</td><td>ndle, 6.0 mm.</td><td>Ð</td><td>2831-10</td><td>1x3.0</td><td>1x4.0</td><td>1x5.5</td><td>1x6.5</td><td></td></t<>	2831-00	SoftFinish <sup>®</sup> electric slimVario bit holder with har	ndle, 6.0 mm.	Ð	2831-10	1x3.0	1x4.0	1x5.5	1x6.5	
onto blade.       O       2831-00       Bit holder with handle         Handle:       Wiha SoftFinish® electric multi-component handle with roll-off protection.       O       2831-00       Bit holder with handle         Bit holder:       ClicFix quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits.       Order-No.       Series       Image: ClicFix quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits.         Note:       Not for use with bit forms C 6.3 and E 6.3.       Image: ClicFix quick release holder securely locks bits.       Image: ClicFix quick release holder securely locks bits.         Note:       Not for use with bit forms C 6.3 and E 6.3.       Image: ClicFix quick release holder securely locks bits.       Image: ClicFix quick release holder securely locks bits.         Vine Werkzeuge GmbH       Image: ClicFix quick release for the protection.       Image: ClicFix quick release for the protection.       Image: ClicFix quick release for the protection.         Wiha Werkzeuge GmbH       Image: ClicFix quick release for the protection.         Wiha Werkzeuge GmbH       Image: ClicFix quick release for the protection.         Image: ClicFix qui				Ð	2831-11	1xPH1	1xPH2			
Handle:Wiha SoftFinish® electric multi-component handle with roll-off protection.Bit holder:ClicFix quick release holder securely locks bits. Only for 6 mm VDE interchangeable bits.Application:Compact screwdriver together with VDE interchangeable bits.Note:Not for use with bit forms C 6.3 and E 6.3.Order-No.SeriesOrder-No. $4 = 30$ Order-No. $4 = 30$ Order-No. $5 = 2831-10$ $1 \times 2.5$ $1 \times 3.0$ $1 \times 4.722$ $2 \times 3.1-10$ $1 \times 4.722$ $1 \times 3.0$ $2$				0	2831-00	Bit holde	er with han	dle		
altroitedaltroitedaltroitedaltroitedaltroitedaltroitedaltroitedaltroitedolide is collected interchangeable bits.Note:Not for use with bit forms C 6.3 and E 6.3.Order-No.O $\rightarrow$ Order-No.O $\rightarrow$ altroited $\rightarrow$ 34577 8650form $\rightarrow$ altroited $\rightarrow$ Order-No. <td>Handle:</td> <td></td> <td>th roll-off protection.</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	Handle:		th roll-off protection.							
Application: Compact screwdriver together with VDE interchangeable bits. Note: Not for use with bit forms C 6.3 and E 6.3. $ \begin{array}{ccccccccccccccccccccccccccccccccccc$	Bit holder:	ClicFix quick release holder securely locks bits. Only	y for 6 mm VDE	Order-No.						
Note:       Not for use with bit forms C 6.3 and E 6.3.         Order-No.       O       Image: Comparison of the comparison of		interchangeable bits.		<b>34734</b> 5	2831 T70	2				1
Note:       Not for use with bit forms C 6.3 and E 6.3.         Order-No.       O       Image: Constraint of the state of the st	Application:	Compact screwdriver together with VDE interchang	eable bits.	Ф	2831-10			1x4.0	1x5.5	
Order-No.       O       Image: Constraint of the second se				$\oplus$	2831-11					
34577 8       6       50       160       30       5         Wiha Werkzeuge GmbH Obertalstraße 3-7 D-78136 Schonach/Germany Tel. + 49 7722 959-0 Fax.+ 49 7722 959-159 info@wiha.com www.wiha.com       Series       Image: Comparison of the series of				0	2831-00	Bit holde	er with han	dle		
Wiha Werkzeuge GmbH Obertalstraße 3-7 D-78136 Schonach/Germany Tel, + 49 7722 959-0 Fax, + 49 7722 959-159 info@wiha.com www.wiha.com         Order-No.         Series         Image: Comparison of the comparison of					~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	AC 1000V				
Obertalstraße 3-7         OrderHot.         OderHot.         OderHot. </td <td></td> <td>Wibe Werkzeure CmbH</td> <td></td> <td></td> <td></td> <td>- icc 00900:200</td> <td>•</td> <td></td> <td></td> <td></td>		Wibe Werkzeure CmbH				- icc 00900:200	•			
Tel. + 49 7722 959-0     ①     2831-10     1x3.0     1x4.0     1x5.5     1x6.5       SDD     mo@wiha.com     ①     2831-14     1xSL/PZ1     1xSL/PZ2	Q	Obertalstraße 3–7								
Support         Fax.+ 49 7722 959-159 info@wiha.com www.wiha.com         (1)         2831-10         1x3.0         1x4.0         1x5.5         1x6.5           (2)         2831-14         1xSL/PZ1         1xSL/PZ1         1xSL/PZ2         1x6.5	TUV									1
www.wiha.com	and the second se	Fax.+ 49 7722 959-159							1x6.5	
O 2831-00 Bit holder with handle	100 9001									
				0	2831-00	Bit holde	er with han	dle		