

## M12 D-cod 4-pol an/- m/- RAIL PP 7.5m




Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                     |
|--------------------|-------------------------------------------------------------------------------------|
| Part number        | 21 40 420 0447 075                                                                  |
| Specification      | M12 D-cod 4-pol an/- m/- RAIL PP 7.5m                                               |
| HARTING eCatalogue | <a href="https://harting.com/21404200447075">https://harting.com/21404200447075</a> |

### Identification

|               |                             |
|---------------|-----------------------------|
| Category      | System cabling              |
| Series        | Circular connectors M12     |
| Element       | Cable assemblies            |
| Specification | Pre-assembled on one side   |
| Connector 1   | M12 D-coding<br>Male Angled |

### Version

|                    |             |
|--------------------|-------------|
| Cable length       | 7.5 m       |
| Number of cores    | 4           |
| Core structure     | 4x AWG 22/7 |
| Shielding          | Shielded    |
| Number of contacts | 4           |
| Coding             | D-coding    |
| Locking type       | PushPull    |

### Technical characteristics

|                                        |                                                |
|----------------------------------------|------------------------------------------------|
| Rated voltage                          | 48 V AC<br>60 V DC                             |
| Transmission characteristics           | Cat. 5 Class D up to 100 MHz                   |
| Limiting temperature                   | -25 ... +70 °C moved<br>-40 ... +85 °C unmoved |
| Degree of protection acc. to IEC 60529 | IP65 / IP67 mated condition                    |
| Cable diameter                         | 6.6 mm ± 0.2 mm                                |



**Pushing Performance**  
Since 1945

## Technical characteristics

|                        |                                      |
|------------------------|--------------------------------------|
| Minimum bending radius | 5x Cable diameter (singular bending) |
|                        | 6x Cable diameter (repeated bending) |

## Material properties

|                                      |                                                        |
|--------------------------------------|--------------------------------------------------------|
| Material (cable)                     | Polyolefin copolymer                                   |
| Colour (cable)                       | Black                                                  |
| RoHS                                 | compliant with exemption                               |
| RoHS exemptions                      | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                           | compliant with exemption                               |
| China RoHS                           | 50                                                     |
| REACH Annex XVII substances          | Not contained                                          |
| REACH ANNEX XIV substances           | Not contained                                          |
| REACH SVHC substances                | Yes                                                    |
| REACH SVHC substances                | Lead                                                   |
|                                      | Triphenyl phosphate                                    |
| ECHA SCIP number                     | 760691ac-b4d2-427c-9996-5886190b813b                   |
| California Proposition 65 substances | Yes                                                    |
| California Proposition 65 substances | Lead                                                   |

## Specifications and approvals

|                |              |
|----------------|--------------|
| Specifications | UN/ECE-R 118 |
|                | EN 45545     |

## Commercial data

|                                |                                              |
|--------------------------------|----------------------------------------------|
| Packaging size                 | 1                                            |
| Net weight                     | 1 g                                          |
| Country of origin              | Romania                                      |
| European customs tariff number | 85444290                                     |
| GTIN                           | 5713140341197                                |
| eCl@ss                         | 27060390 Ready-made data cable (unspecified) |
| ETIM                           | EC002599                                     |
| UNSPSC 24.0                    | 26121600                                     |