

## Data sheet

264-304

### 2-CONDUCTOR END TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE



## Technical data

Package size 100 pieces.

Cross section from [mm <sup>2</sup> ]	0.08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2.5 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Voltage UL	600 V
Voltage CSA	600 V
Current UL	20 A
Current CSA	20 A
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	3.9 g
Color	blue
Wiring type	Front-entry
No. of connection Points	2
No. of potentials	1
Height	22 mm
Height	0.867 in
Width	6 mm
Width	0.236 in
Depth	32 mm
Depth	1.26 in

---

Data sheet

264-304

**2-CONDUCTOR END TERMINAL BLOCK CENTRE MARKING  
FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**

---

Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in

## Data sheet

264-304

### 2-CONDUCTOR END TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

---

Approval	Voltage	Current	Approval number	Notes
BBJ	800	24	B/12/696/03	
BV			07436/C0	
CCA	800	24	DK96-00357	
CSA	600	20	18677-23	
CSM	800	24	017956	
DEMKO		24	120040/120039/04	
DNV	800	24	E6998	
GL	800	24	17295-00HH	
KEMA	750		94.7117.01	
KR	800	24	HMB05880-EL002	
LR	800	24	91/20242(E3)	
PRS	800	24	TE/1219/880590/98	
RMR	800	24	99.00007.250	
RosTesT	800	24	B09523	
SEMKO			9404012	
SEV-EX	800	24	97,550142,1	
UL	600	20	E45172	
VDE	660		3945ÜG,BL.2	

## Data sheet

264-304

## 2-CONDUCTOR END TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

### Accessories

### Item number

ALTERNATE COMB TYPE JUMPER BAR INSULATED	281-492
COMB TYPE JUMPER BAR INSULATED	264-402
COVER CARRIER TYPE 1	709-167
COVER TYPE 1	709-153
END PLATE WITH FIXING FLANGE	264-361
END PLATE WITH FIXING FLANGE	264-364
Individual wire jumpers	individual jumper
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-002
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-005
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-006
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-007
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-012
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-017
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-023
MINIATURE WSB QUICK MARKING SYSTEM PLAIN	248-501/000-024
MODULAR TEST PLUG ADAPTER MODULAR	249-136
Open individual wire jumpers ends	individual jumper open end
OPERATING STICKER FOR FRONT-ENTRY MINIATURE RAIL-MOUNTED TERMINAL BLOCKS	210-291
OPERATING TOOL FITTED FOR SERIES 264, 280, 281	209-130
OPERATING TOOL INSULATED	280-432
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-258
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620
SPARE FIXING / RETAINING SCREWS	209-196
SPARE KNURLED NUT	210-549
TEST PLUG 2 MM / 0.079 IN WIDE	210-136
TEST PLUG 2.3 MM / 0.091 IN WIDE	210-137