

V1_10052018_01_en

Wire Wrapping Wire, PVDF insulated, 15M /roll



Ideally suited for wire wrapping and many other applications.

Wire wrapping - making solderless connections of wire to terminals remains the preferred method for both automatic and semi-automatic termination in the wiring of computer backpanels.

The wire is silver plated solid copper, Kynar[®]insulated with 105°C insulation temperature.



	Conductor		Insulation		Electric characters						
Wire size AWG	Diameter(mm)	cross section(mm ²)	Average wall thickness(mm)	Overall Diameter(mm)	Voltage rating (V/min)	Temperature rating(°C)	Spark test (V/sec.)	strength(VDC)	max. Conductor resistance (Ω /kM)	Elongating % (before insulation)	Tensile strength (Kgf/mm ²⁾
24	0.5±0.01	0.196±0.001	0.125±0.01	0.75±0.02	300	105	500/0.15	1000	76.4	20	0.95
26	0.4±0.01	0.1256±0.001	0.115±0.01	0.63±0.02	300	105	500/0.15	1000	122	20	0.95
28	0.31±0.01	0.0804±0.001	0.11±0.01	0.53±0.02	300	105	2000/0.1	1000	232	20	0.85
30	0.24±0.01	0.0491±0.001	0.105±0.01	0.45±0.02	300	105	1000/0.1	1000	340	20	0.75
32	0.20±0.01	0.0311±0.001	0.075±0.005	0.35±0.01	300	105	100/0.15	900	597	20	0.55
34	0.16±0.01	0.0201±0.001	0.065±0.005	0.29±0.01	300	105	1500/0.15	900	920.8	20	0.55
36	0.12±0.01	0.0113±0.001	0.065±0.005	0.25±0.01	300	105	1500/0.15	900	1361	20	0.55

This is a publication by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau (www.conrad.com).

All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval by the editor. Reprinting, also in part, is prohibited. This publication represents the technical status at the time of printing.

© Copyright 2018 by Conrad Electronic SE.



Distributed by Conrad Electronic SE • Klaus-Conrad-Str. 1 • D-92240 Hirschau
Datasheet

V1_10052018_01_en

2

Wire Size AWG	ltem No.	Colour		
	1571386	Black		
	1571387	White		
	1571388	Grey		
	1571389	Blue		
24	1572157	Yellow		
	1572158	Orange		
	1572159	Red		
	1572160	Brown		
	1572161	Purple		
	1566844	Yellow		
	1566845	Red		
26	1566846	Black		
	1566847	White		
	1566855	Green		
	1564480	Red		
	1564481	Black		
	1565160	Grey		
28	1565161	Blue		
20	1566856	Yellow		
	1566857	White		
	1566858	Purple		
	1566859	Green		
	1564482	White		
	1565162	Orange		
	1565163	Blue		
	1565164	Green		
30	1566860	Yellow		
	1566861	Red		
	1566862	Brown		
	1566863	Black		
	1566864	Grey		

This is a publication by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau (www.conrad.com).

All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval by the editor. Reprinting, also in part, is prohibited. This publication represents the technical status at the time of printing.

© Copyright 2018 by Conrad Electronic SE.



Distributed by Conrad Electronic SE • Klaus-Conrad-Str. 1 • D-92240 Hirschau
Datasheet

V1_10052018_01_en

3

Wire Size AWG	Item No.	Colour			
	1564483	Yellow			
	1565165	Black			
	1566865	Red			
32	1566866	White			
	1566867	Grey			
	1566868	Blue			
	1566869	Green			
	1564484	Red			
	1566870	Black			
34	1566871	Blue			
	1566872	Green			
	1570179	Yellow			
	1565166	Red			
	1565167	Blue			
	1566873	White			
36	1566874	Grey			
	1566875	Green			
	1570180	Yellow			
	1570181	Black			

This is a publication by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau (www.conrad.com).

All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval by the editor. Reprinting, also in part, is prohibited. This publication represents the technical status at the time of printing.

© Copyright 2018 by Conrad Electronic SE.