



Male plug-in connector - Faston type: 4.8x0.8 - Pitch 5mm - Double PIN - 02÷30 poles

GENERAL INFORMATION

pitch:	5 mm
housing height:	12,65 mm
housing depth:	9.7 mm
dimensional class:	n/a
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-°C ÷ +°C

ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	250V
impulse voltage:	4 kV

MECHANICAL CHARACTERISTICS

APPROVALS DATA



current:
voltage:
FILE:

-
-
-

-
-
-

UL 1059
18A factory / 15A field
300V
E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a

AVAILABLE COLOURS



other colours:

upon request

terminal:

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PVSF02-5-V-D48-1F	N/A	N/A	N/A
03	PVSF03-5-V-D48-1F	N/A	N/A	N/A
04	PVSF04-5-V-D48-1F	N/A	N/A	N/A
05	PVSF05-5-V-D48-1F	N/A	N/A	N/A
06	PVSF06-5-V-D48-1F	N/A	N/A	N/A
07	PVSF07-5-V-D48-1F	N/A	N/A	N/A
08	PVSF08-5-V-D48-1F	N/A	N/A	N/A
09	PVSF09-5-V-D48-1F	N/A	N/A	N/A
10	PVSF10-5-V-D48-1F	N/A	N/A	N/A
11	PVSF11-5-V-D48-1F	N/A	N/A	N/A
12	PVSF12-5-V-D48-1F	N/A	N/A	N/A
13	PVSF13-5-V-D48-1F	N/A	N/A	N/A
14	PVSF14-5-V-D48-1F	N/A	N/A	N/A
15	PVSF15-5-V-D48-1F	N/A	N/A	N/A
16	PVSF16-5-V-D48-1F	N/A	N/A	N/A
17	PVSF17-5-V-D48-1F	N/A	N/A	N/A
18	PVSF18-5-V-D48-1F	N/A	N/A	N/A
19	PVSF19-5-V-D48-1F	N/A	N/A	N/A
20	PVSF20-5-V-D48-1F	N/A	N/A	N/A
21	PVSF21-5-V-D48-1F	N/A	N/A	N/A
22	PVSF22-5-V-D48-1F	N/A	N/A	N/A
23	PVSF23-5-V-D48-1F	N/A	N/A	N/A
24	PVSF24-5-V-D48-1F	N/A	N/A	N/A