

## Side Cutter Side cutter, semi flush cut, burnished, ESD safe, max. Cu 0,6 mm, 110 mm, 61 g

## Marketing Texte

Long description	Side cutter, semi flush cut, burnished, ESD safe, max. Cu 0,6 mm, 110 mm, 61 g
Short description	Side Cutter
Packaging information	
Shelf pack size (Units per shelf pack)	Single
Technical Data	
Cut type	Semi Flush
Head size	Medium
Hardness classes	Soft
Head shape	Side Cutters
Hardening type	Induction
Handle / grip material	Foam coated
Operation mode	One-handed
Material hardness	Cu
Material to be cut	Metal
Steel type	Tool steel
Surface finish	Anti-glare



Services available	Sharpening and Spare parts
Erem Technology	<ul> <li>Internal patented Erem Magic Spring: for constant spring force and more than 1 million cutting cycles guaranteed</li> <li>High Precision screw joint: for smooth cutting action and wobble free operation with no blade overlap</li> <li>Introduction hardened blades in Rockwell hardness 63-65 HRc: for exceptionally long life</li> <li>EMOS maximum opening stop: Reduces operator fatigue by preventing excessive hand spread</li> </ul>
Material Diameter or thickness MAX	0.6
Material Diameter or thickness MIN	0.03
ESD safe	No
Opening spring	No
Handle cushioned	No
Slip stop	No