

ATPH 1850-0200



Alu-Topline
Enclosure profiles, horizontally-divided
Order no.: 92850200

Colour of enclosure group

Natural-coloured anodised aluminium profile; plastic lid quartz grey, similar to RAL 7039 or graphite grey, similar to RAL 7024; special colours on request

Protection class


IP 40/DIN EN 60529; IP 54/DIN EN 60529 as an option

Enclosure material

Extruded profiles: Al Mg Si 0.5 anodised; plastic lid: ABS; for details see Technical Information

Scope of delivery: Enclosure profile, 2 parts

Note: Special lengths on request.



A 181,2 mm
B 53,2 mm
C 200 mm

Technical drawings

3D product data in STEP format:

[Registration necessary](#)

Catalogue drawing in DXF format:

[92850200_ATPH-1850-0200.dxf](#) (490 KB)

Basic drawing for processing work:

[92850200_ATPH-1850-0200-G.dxf](#) (422 KB)

Catalogue drawing in PDF format:

[92850200_ATPH-1850-0200.pdf](#) (42 KB)

Assembly instructions

[Alu-Topline-AT-0...-7024-UWB.pdf](#) (500 KB)

Chapter download


[Alu-Topline_GB.pdf](#) (326 KB)

Accessories



End cover

- 92050024 [ATD](#) For ATPH 1850 Graphite grey
[1850-7024](#)
- 92050039 [ATD](#) For ATPH 1850 Quartz grey
[1850-7039](#)



Seals for ingress protection IP 54

- 92050000 [AT 1850 DI](#) For ATPH 1850



Wall fastening, aluminium

- 92800200 [AT 1800-0200](#) For ATPH-0200
[WB](#)



Universal wall fitting

- 92820024 [AT 0200-7024](#) For ATPH-0200 Graphite grey
[UWB](#)



Insulating strip for PCB mounting on the profile

- 92000100 [AT-IS 00020](#) Length: 101,5 mm



Rubber feet

- 84006700 [AB - GF](#) Polyurethane, 65-75 Shore Black

* = Available on request