


Data sheet Product SL 4 025 ...




PCB connectors>Male headers
male header □ 0.635 mm, "dimensions A + B" changeable

Features

grid:	2.54 mm
no. of contacts:	2 - 72
contact material:	CuSn alloy
surface of contact:	<ul style="list-style-type: none">• selective gold-plated• gold-plated• tin-plated
surface contact / contact sleeve:	<ul style="list-style-type: none">• Ni+≥0.2μm Au• Ni+4...6μm Sn
version:	insertion side "dimension C", "S" selective gold-plated
volume resistance:	≤5 mΩ
nominal current:	3 A
nominal voltage:	250 V AC
test voltage:	2000 V
insulating body material:	PA 4.6. GF
temperature range:	<ul style="list-style-type: none">• -40°C... +163°C• (260°C/10 s)
class of inflammability:	UL 94 V-0
specific insulation resistance:	>10 ⁷ Ω·m
connection type:	THT (soldering)
reflow solderable:	yes

Technical Drawing



A:	4.5 mm
B:	3 mm
C:	5.8 mm
S:	5.0 mm

Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28
58511 Lüdenscheid

Telefon +49 2351 435-0
Telefax +49 2351 45754

info@fischerelektronik.de
www.fischerelektronik.de