

Interzoll | PCB holder and fixing material



BFS/M 2000

Order no.:86000200

MU M 2.5-6KT, galvanised steel, for LKH/M 02

* = Available on request.

Configure mast mounting



Quickly and easily configure the appropriate modules based on your requirements to obtain the optimal mast mounting solution for your application.

» Configure now

Important: Suitable pressure compensation element



To compensate for pressure when temperatures change and cause moisture in the enclosure, we recommend that you use a **pressure compensation** element.

In order to ensure that you can determine the correct quantity of elements for your application, we are providing you here with a DAE calculator.

» Calculate now

—

Profile Al Mg: Si 0.5; for details see Technical Information

BFS/M: 20 pieces

[illegible]


KPSA
 KUTUP SANAYİ VE TİCARET A.Ş.

Interzoli


KPSA
 KUTUP SANAYİ VE TİCARET A.Ş.

Enclosure sizes

Design types

Dimensions

Model	Height	Width	Depth	Weight	Material
100	100	100	100	1.5	Aluminum
150	150	150	150	2.5	Aluminum
200	200	200	200	3.5	Aluminum
250	250	250	250	4.5	Aluminum
300	300	300	300	5.5	Aluminum
350	350	350	350	6.5	Aluminum
400	400	400	400	7.5	Aluminum
450	450	450	450	8.5	Aluminum
500	500	500	500	9.5	Aluminum
550	550	550	550	10.5	Aluminum
600	600	600	600	11.5	Aluminum
650	650	650	650	12.5	Aluminum
700	700	700	700	13.5	Aluminum
750	750	750	750	14.5	Aluminum
800	800	800	800	15.5	Aluminum
850	850	850	850	16.5	Aluminum
900	900	900	900	17.5	Aluminum
950	950	950	950	18.5	Aluminum
1000	1000	1000	1000	19.5	Aluminum

Assembly

09.06.2026

