

Wiha SoftFinish® electric slimFix.

Easy to handle for electrical applications with particulary slim blade.





Available as of

January 25, 2010 POS support:

- Product introduction leaflet
- Product brochure
- Display



- Protective insulation is completely integrated in the front area of the blade
- Particulary slim diameter of 38 mm allows easy access to low lying fastening elements or spring terminals
- Individually tested in water bath at 10,000 Volts according to IEC 60900:2004
- Safe working on live parts up to 1000 V AC or 1500 V DC
- Awarded the GS symbol for tested safety
- Ergonomic handle geometry with SoftFinish[®] surface guarantees highest levels of comfort
- Skin-friendly soft zone in the upper handle for effortlessly achieving required torque



SoftFinish® electric slimFix slotted screwdriver.
Insulation 1000 V AC, VDE-tested and with GS mark.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black finish. The integrated protective insulation is directly moulded onto the blade and completely integrated in front area.

Handle: Wiha SoftFinish® electric multi-component handle with roll-off protection.

Standards: DIN 7437, DIN 5264, DIN ISO 2380. Manufactured acc. to IEC 60900:2004.

Application: For all work on or around electrical components up to 1000 V AC.

Extra: The particulary slim diameter of the blade with integrated protective insula-

The particulary slim diameter of the blade with integrated protective insulation enables low lying fastening elements and spring terminals to be

reached and operated easily.

| Order-No. | Φ | = | •1 | === | _ | | € /pc. |
|----------------|-----|----------|-----|-----|--------------|----|---------------|
| 35446 6 | 3,5 | 100 | 0,6 | 204 | 23 | 10 | 7,65 |
| 35390 2 | 4,0 | 100 | 0,8 | 211 | 30 | 10 | 9,10 |
| 35391 9 | 5,5 | 125 | 1,0 | 243 | 36 | 10 | 11,00 |
| 35392 6 | 6,5 | 150 | 1,2 | 268 | 36 | 10 | 14,30 |





3211 SoftFinish® electric slimFix Phillips screwdriver.

Standards: DIN 7438, DIN ISO 8764. Manufactured acc. to IEC 60900:2004.

| Order-No. | ⊕ | | == | — <u></u> | | €/pc. |
|----------------|----------|---------|-----|------------------|----|-------|
| 35393 3 | PH1 | 80 | 191 | 30 | 10 | 10,20 |
| 35394 0 | PH2 | 100 | 218 | 36 | 10 | 13,70 |





SoftFinish® electric slimFix Pozidriv screwdriver.

Standards: DIN 7438, DIN ISO 8764. Manufactured acc. to IEC 60900:2004.

| Order-No. | ₩ | | == | — <u></u> | | € /pc. |
|----------------|-----|---------|-----|------------------|----|---------------|
| 35395 7 | PZ1 | 80 | 191 | 30 | 10 | 11,20 |
| 35396 4 | PZ2 | 100 | 218 | 36 | 10 | 15,40 |

Wiha Werkzeuge GmbH Obertalstraße 3–7 D-78136 Schonach/Germany Tel. + 49 7722 959-0 Fax.+ 49 7722 959-159 info@wiha.com





Also available as set:







